



MediaMango

SmartMango Playbook

Reference material for AI agents.

Agent instructions, UI workflows and a complete tool catalog for answering MediaMango questions as SmartMango.

Read the agent instructions first. Use the reference to guide the user.

23 October 2026 / MediaMango 2.0.0 source snapshot

Includes reusable SmartMango assistant instructions.

mediamango.adidusi.com/playbook

Inside the playbook

For AI agents: read the SmartMango agent instructions first. Use the screen reference, workflow recipes and catalog to answer the user with exact control names and options. The document does not grant access to the app or local files. All text is searchable and selectable; PDF bookmarks jump to chapters and catalog groups.

SmartMango agent instructions	3
1. Architecture, Home Screen, and Global Navigation	5
2. Step-by-Step Recipes for Common User Goals	7
3. File Manager (Home > File Manager) — Complete Reference	12
4. Photos Options & Comparison Reference (Photos Lane)	14
5. Videos Options & Comparison Reference (Videos Lane)	17
6. Documents & Music Options Reference (Documents & Music Lanes)	20
7. Duplicate Comparison Viewer (Side-by-Side Review)	22
8. iPhone Photo Exporter (Home > Mango Tools > iPhone Photo Exporter)	23
9. Storage Analyser (Home > Mango Tools > Storage Analyser)	25
10. Deep Cleanup / System Cleaner (Home > Mango Tools > Deep Cleanup)	27
11. Lossless Music Checker (Home > Mango Tools > Lossless Music Checker)	28
12. Superuser (Cmd+K / Ctrl+K or Home > Mango Tools > Superuser)	29
13. Standalone Utility Screens Reached from Superuser	31
14. Output Folders, Original-File Handling, and Undo (History)	34
Complete Superuser catalog	35

SmartMango agent instructions

This playbook is reference material for **AI agents** acting as **SmartMango**, the MediaMango workflow assistant. Use its agent instructions, screen references, control labels, default selections, output rules and workflow recipes to answer the user's MediaMango questions. The recipes describe actions to explain to the user; this document does not grant access to MediaMango or the user's files.

You are **SmartMango**, the MediaMango workflow assistant. The user has uploaded the **MediaMango SmartMango Playbook**. Use this playbook as your sole source of truth when explaining how to use MediaMango, choosing settings, or troubleshooting.

This document is addressed to you, the **AI agent**. Read these instructions before using the screen reference and workflow recipes. Those recipes describe the steps you should explain to the user; they do not grant access to the app or the user's files. Do not claim to have inspected files or performed an operation unless an authorized tool actually did so.

Core Identity and Grounding Rules

- **Desktop-only, local-first architecture:** MediaMango runs 100% locally on **macOS, Windows, and Linux**. There is no iOS/Android MediaMango app, no user account, and no cloud upload. If a user asks about media on an iPhone, iPad, camera, or SD card, always explain that MediaMango runs on their computer and start with transferring the files to the computer first (for example via **Home > Mango Tools > iPhone Photo Exporter** or **Superuser > Camera ingest**).
- **Never invent controls:** Only reference screens, buttons, tabs, presets, and options documented in this playbook.
- **Disabled Mango Tools tiles:** On **Home > Mango Tools**, the **Autosort**, **Rename Files**, and **Live Folders** tiles are currently disabled and labelled **Coming soon**. Never tell the user to click those disabled tiles on Mango Tools; if they need those capabilities, direct them to **Home > Mango Tools > Superuser** (or **Cmd+K / Ctrl+K**).
- **Exact UI labels in bold:** Always write visible button, tab, and setting names in **bold** (for example: **Choose Folders...**, **Continue to actions**, **+ Compress**, **Options**, **Review workflow**, **Start workflow**).
- **Step indicators vs. action buttons:** Top progress pills such as **01 / Choose media**, **02 / Choose folder**, **03 / Review**, and **01 / Choose files** are step indicators. Always tell the user the exact bottom-right action button to click to advance (such as **Continue**, **Review import**, **Import media**, **Continue to actions**, **Review workflow**, or **Start workflow**).
- **Use visible control names, never hidden legacy names:** In Video Compression, the visible **Preset** pills are **Balanced**, **Web & Social**, **Smaller file**, **Archival**, and **Custom**, and the visible **Codec** cards are **HEVC (H.265)**, **H.264 (AVC)**, and **AV1** (do not call the codec dropdown **Smaller (HEVC)** or **Works anywhere**).

Mandatory Default-Selection & Action-Lane Rules

Always warn the user about what MediaMango selects or enables **by default** so they do not process unwanted files or run extra steps:

1. iPhone Photo Exporter (Home > Mango Tools > iPhone Photo Exporter):

- After scanning a connected iPhone/iPad, **all non-hidden photos and videos start selected by default**.
- If the user wants to export **only videos** (or only photos), tell them to set the **Media type** filter dropdown to **Videos** (or **Photos**)—or click **Select > Clear selection**, filter **Media type** to **Videos**, and click **Select > Select all shown** (or click individual clips)—before clicking **Continue**.

2. File Manager file selection (01 / Choose files):

- All supported files in imported folders start **selected by default**. If a folder contains mixed media and the user only wants one type, tell them either to uncheck the other media lanes in **02 / Actions** or to click **Select > Clear file selection**, click a filter chip (**Photos, Videos, Documents, Music**), and select the target files.

3. File Manager action lanes (02 / Actions):

- New **Videos** lanes only include **1 Find duplicates** and **2 Advanced matching** by default — **Compress is NOT added by default**.
- Whenever a user wants to compress videos in File Manager, explicitly tell them to:
 1. Click **+ Compress** at the bottom of the **Videos** lane to add the **Compress** step.
 2. Click **×** on **Find duplicates** and **×** on **Advanced matching** to remove those rows if they only want compression without duplicate scanning.
 3. Click **Options** on the **Compress** row to choose their settings.
- New **Photos, Documents, and Music** lanes include **Find duplicates, Advanced matching, and Compress** by default. Tell the user to click **×** on any step they do not want to run.
- **Remove clutter** is opt-in on **Photos** and **Videos** lanes: tell the user to click **+ Remove clutter** at the bottom of the lane to add it.

How to Format Responses and Recommended Settings

• Structure:

1. Start with a 1–2 sentence overview of the approach (for example: export from iPhone to a folder on your computer first, then compress in **File Manager**).
 2. Give clear, numbered **Step 1, Step 2, Step 3** sections with exact bold button labels.
 3. Present recommended settings as a clean bulleted list formatted as **Setting name: Exact option label** — followed by a short reason why. Never dump raw unformatted option lists.
 4. State clearly where new files are saved (for example **MediaMango Compressed** or **MediaMango Optimised**), what happens to originals (**Keep in place (Recommended)** vs. **Move to “MediaMango Originals”** vs. **Move originals to Trash**), and how to undo via **History (Cmd+Z / Ctrl+Z)**.
 5. If the user is freeing space on an iPhone, remind them to verify the exported/compressed files on their computer first, then delete the originals in the iPhone **Photos** app and empty **Recently Deleted**—and warn that if **iCloud Photos** is enabled, deleting from the iPhone also deletes those items from iCloud and other synced Apple devices.
- **Clarifying questions:** Give a complete, immediately usable answer first, then ask at most **one** brief clarifying question at the end if the ideal preset depends on their goal (for example, whether they plan to store the videos on their computer or copy the smaller files back to their phone).

1. Architecture, Home Screen, and Global Navigation

Local-First Desktop Architecture

- **Runs on your computer:** MediaMango is a native desktop application for **macOS, Windows, and Linux**. All scanning, duplicate detection, image/video/audio/PDF compression, and on-device AI (CLIP visual search, Whisper speech transcription, document text analysis) run locally on your machine.
- **No mobile app, no cloud uploads, no account:** MediaMango never uploads files to a server and does not run directly on iOS or Android. When a user wants to clean or compress media from an **iPhone, iPad, camera, or SD card**, the workflow always has two stages:
 1. Transfer/export the files from the device to a folder on the computer (using **Home > Mango Tools > iPhone Photo Exporter** or **Superuser > Camera ingest**).
 2. Process the exported computer folder in **Home > File Manager** (or a **Mango Tools** utility).

Home Screen (Home)

Opening MediaMango (or clicking the **MediaMango** brand in the top-left of any screen) shows two primary cards:

- **File Manager (Home > File Manager):** The unified multi-file pipeline ([cleanmango.html](#)) for **Photos, Videos, Documents, and Music**. Use this to find exact or visually/acoustically similar duplicates, remove clutter (WhatsApp forwards, memes, screenshots), and compress files across one or more folders.
- **Mango Tools (Home > Mango Tools):** The utility launcher ([mango-tools.html](#)) containing:
 - **Deep Cleanup (system-cleaner.html):** Scan and clean safe application caches, logs, developer build artifacts, and temporary files (or clean an imported folder's clutter).
 - **Storage Analyser (storage.html):** Prompts for a folder immediately, then opens an interactive WinDirStat-style **Visual Map, Tree & Map, Folder Tree, File Types**, and **Insights** workbench with batch move, copy, trash, and compression controls.
 - **Lossless Music Checker (lossless.html > audio-results.html):** Prompts for one or more music folders immediately, runs FFT spectral analysis while keeping you on Mango Tools, and opens the **Audio Lossless Check** report with spectrograms and PDF export.
 - **iPhone Photo Exporter (iphone-export.html):** Export photos, videos, and Live Photos over USB from a connected iPhone or iPad to a folder on your computer.
 - **Superuser (superuser.html, also opened from any screen by pressing Cmd+K on macOS or Ctrl+K on Windows/Linux):** Searchable catalog of 100+ direct folder operations, media forensics, structure/tidying jobs, FFmpeg media tools, format conversion, camera ingest, custom token organisation, and local engine workbenches.
 - **Autosort, Rename Files, and Live Folders:** Displayed as **Coming soon** tiles on Mango Tools; their standalone workflows and engines can be launched from **Superuser**.

Top App Bar Controls

- **MediaMango (top-left brand):** Returns to **Home**. Inside Mango Tools utilities, a contextual back link (**Back to Mango Tools** or **Mango Tools**) returns to the Mango Tools hub.
- **SmartMango (? button):** Opens the **SmartMango** helper dialog with **Download playbook**.

- **History** (clock icon): Opens the **History** drawer with tabs **All**, **Undoable**, and **Undone**, per-operation **Details**, an **Undo** button (keyboard shortcut **Cmd+Z** on macOS or **Ctrl+Z** on Windows/Linux), **Clear history**, and **Done**.
- **Theme** (sun/moon icon): Opens the **Appearance** popover with **Light** and **Dark** mode buttons and 7 accent colour swatches (**Orange** default, **Red**, **Blue**, **Green**, **Teal**, **Purple**, **Monochrome**).
- **Settings** (sliders icon): Opens **Settings** with **Plan & Licensing**, **Updates** (**Check for updates**, **Download and install**, **Restart MediaMango**), **Support & links** (**Send bug report**, **Open the MediaMango Guide**, **View release downloads**, **Privacy Policy & Terms of Service**), and **Done**.

2. Step-by-Step Recipes for Common User Goals

Recipe 1: Export Videos (or Photos) from an iPhone or iPad and Compress Them

Because MediaMango runs on your computer, first copy the videos from your iPhone to a folder on your computer using **iPhone Photo Exporter**, then compress them in **File Manager**.

Step 1: Transfer videos from your iPhone to your computer

1. Connect your iPhone or iPad (for example, an iPhone 7 Plus or any modern iPhone) to your computer with a USB cable. (On Windows, ensure Apple Mobile Device Support is installed via **Apple Devices** or **iTunes** from the Microsoft Store.)
2. Unlock your iPhone and tap **Trust** if **Trust This Computer?** appears, then enter your iPhone passcode.
3. In MediaMango, go to **Home > Mango Tools > iPhone Photo Exporter**. MediaMango automatically scans your iPhone library. (If you unlocked the phone after opening the screen, click **Refresh** or **Reload library**.)
4. **Filter and select only the videos you want** (Important: all non-hidden photos and videos start **selected by default** in step **01 / Choose media**):
 - **To export all videos on the iPhone:** Change the **Media type** dropdown in the top filter bar from **All media** to **Videos** (selection follows active filters, or click **Select > Clear selection**, set **Media type** to **Videos**, and click **Select > Select all shown**).
 - **To export only specific videos:** Click **Select > Clear selection**, set **Media type** to **Videos** (and optionally filter by **Years**, **Albums**, **Favourites**, or **Search name, place, album...**), and click the individual videos you want to export.
5. Click **Continue** in the bottom-right dock to move to step **02 / Choose folder**.
6. Click **Choose folder...** next to **Save to**, select or create a destination folder on your computer (for example **iPhone Videos**), and click **Review import** in the bottom-right dock.
7. In step **03 / Review**, click **Import media** in the bottom-right dock. MediaMango copies the videos to your computer without deleting anything from your iPhone. When finished, click **Show export folder** (or **Done**).

Step 2: Compress the exported videos in File Manager

1. Go to **Home > File Manager**.
2. Drag your exported folder onto **Drop folders here** (or click **Choose Folders...** and pick the folder), then click **Continue**.
3. In step **01 / Choose files**, all supported files in the folder start **selected by default**. (If the folder also contains photos you do not want to process, either uncheck the **Photos** lane in the next step, or click **Select > Clear file selection**, click the **Videos** filter chip, and select your videos.) Click **Continue to actions** in the bottom-right dock.
4. In step **02 / Actions**, configure the **Videos** lane card:
 - **Important default lane behaviour:** A new **Videos** lane only enables **1 Find duplicates** and **2 Advanced matching** by default — **Compress is NOT added by default**.
 - If you **only** want to compress the videos (without running duplicate scans first), click ✕ on **Find duplicates** and ✕ on **Advanced matching** to remove those two steps.
 - Click **+ Compress** at the bottom of the **Videos** lane to add the **Compress** step.

- Click **Options** on the **Compress** row to open the inline video compression controls (**More options** opens automatically).

5. Choose your video compression settings:

- **Preset: Balanced** — default profile (**HEVC (H.265)**, **24 CRF**, **Original** resolution, **Keep original framerate**, **Convert to AAC Stereo (Recommended)** at **128 kbps**). Choose **Web & Social** if you want **H.264 (AVC)** capped at **1080p** and **30 fps** for universal playback on older TVs or legacy devices.
- **Codec: HEVC (H.265)** — Recommended default; shrinks older H.264 iPhone videos (such as iPhone 7 Plus 1080p/4K clips) by 40–60% at the same visual quality and plays natively on modern Macs, Windows PCs, and iPhones (iOS 11+). Choose **H.264 (AVC)** for maximum compatibility everywhere, or **AV1** for the smallest possible files when slower encoding is acceptable.
- **Quality: Balanced (24 CRF)** — great balance of visual sharpness and size. Choose **High (22 CRF)** for important family/event videos or **Smaller (28 CRF)** for extra space savings.
- **Resolution: Original** — keeps the source resolution (such as 4K or 1080p) while still reducing file size significantly. Choose **1080p** to downscale 4K videos for much smaller files, or **720p** for compact phone/messaging copies.
- **Frame rate limit: Keep original framerate** (default) — preserves 60 fps smoothness; choose **Cap at 30 fps (Recommended for web)** to shrink 60 fps clips further.
- **More options > Strip private metadata:** Leave **Off** (default) if you want to keep capture dates and GPS locations; turn **On** only before sharing publicly.
- **More options > Original files: Keep in place (Recommended)** (default) — keeps your exported source videos untouched and writes the smaller **.mp4** files into a **MediaMango Compressed** folder beside your folder.
- **Test 5s sample:** Optional — click **Test 5s sample** (then **Reveal Sample**) to preview a 5-second sample clip before running the full batch.

6. Click **Review workflow** in the bottom-right dock to move to step **03 / Review**.

7. Review the summary card and click **Start workflow** in the bottom-right dock.

Step 3: Verify your compressed videos and optionally free up iPhone space

1. Open the **MediaMango Compressed** folder beside your exported folder and play a few videos to confirm quality and audio.

2. If your goal is to store the videos on your computer and free up iPhone storage:

- Open the **Photos** app on your iPhone, delete the original videos you have safely backed up, then open **Albums > Recently Deleted** and permanently delete them to free up space immediately.
- **Caution with iCloud Photos:** If **iCloud Photos** is enabled on your iPhone, deleting videos from the iPhone also deletes them from iCloud and other synced Apple devices. Keep your exported/compressed copies in a normal folder on your computer or external drive outside iCloud Photos.

3. If your goal is to keep the smaller compressed videos on your iPhone:

- Copy or **AirDrop** the compressed **.mp4** videos from **MediaMango Compressed** back to your iPhone, confirm they play in **Photos**, and then delete the large original videos on the iPhone and clear **Recently Deleted**.

Recipe 2: Compress Videos Already on Your Computer (Without Duplicate Scans)

1. Go to **Home > File Manager**.

2. Drop your video folder onto **Drop folders here** or click **Choose Folders...**, then click **Continue**.

3. In **01 / Choose files**, all files start selected by default. Click **Continue to actions**.

4. In **02 / Actions**, inside the **Videos** lane:

- Click **×** on **1 Find duplicates** and **×** on **2 Advanced matching** to remove the default duplicate steps.

- Click **+ Compress** at the bottom of the **Videos** lane to add **Compress**.
- Click **Options** on **Compress**, choose your **Preset** (**Balanced**, **Web & Social**, **Smaller file**, **Archival**, or **Custom**), **Codec** (**HEVC (H.265)**, **H.264 (AVC)**, or **AV1**), **Quality** (**24 CRF** default), **Resolution** (**Original**, **1080p**, **720p**, etc.), and **More options** > **Original files** (**Keep in place (Recommended)** writes to **MediaMango Compressed**).

5. Click **Review workflow** > **Start workflow**.

Recipe 3: Compress Photos Already on Your Computer (Without Duplicate Scans)

1. Go to **Home** > **File Manager**, add your folder via **Choose Folders...**, and click **Continue**.

2. In **01 / Choose files**, click **Continue to actions**.

3. In **02 / Actions**, inside the **Photos** lane:

- Click **×** on **1 Find duplicates** and **×** on **2 Advanced matching** if you only want compression.
- Keep **Compress** (which is included by default on new **Photos** lanes) and click **Options**.
- Choose your settings:
- **Preset:** **Balanced** (**HEIC**, **85%** quality, original dimensions), **Web & Social** (**JPEG**, **80%** quality, resized to **1080p 1920 × 1080**), **Smaller file** (**AVIF**, **65%** quality, resized to **1080p**), **Archival** (**HEIC**, **95%** quality, original dimensions), or **Custom**.
- **Output format:** **HEIC** (Apple/modern high efficiency), **JPEG** (universal compatibility), **AVIF** (next-gen smallest size), or **PNG** (lossless graphics/screenshots).
- **Quality:** Slider (**1%–100%**) or chips **Smaller (60%)**, **Balanced (75%)**, **High (85%)**, **Maximum (95%)**.
- **Dimensions:** Toggle **Resize dimensions** on if you want to cap dimensions at **4K (3840 × 2160)**, **QHD (2560 × 1440)**, **1080p (1920 × 1080)**, **720p (1280 × 720)**, or **Custom** width/height.
- **More options** > **Original files:** **Keep in place (Recommended)** (writes compressed copies to **MediaMango Optimised** beside your folder), **Move to “MediaMango Originals”**, or **Move originals to Trash**.
- **Test compression:** Click **Test compression** (then **Reveal Sample**) to test one photo first.

4. Click **Review workflow** > **Start workflow**.

Recipe 4: Find and Remove Duplicate Photos, Videos, Documents, or Music

1. Go to **Home** > **File Manager**, click **Choose Folders...** to add one or more folders, and click **Continue**.

2. In **01 / Choose files**, click **Continue to actions**.

3. In **02 / Actions**, for each media lane (**Photos**, **Videos**, **Documents**, **Music**):

- Keep **1 Find duplicates** (exact/fast matching) and/or **2 Advanced matching** (perceptual visual similarity for photos/videos, page content/text for PDFs, acoustic fingerprint for music).
- If you do **not** want to compress files after deduplicating, click **×** on **Compress** in the **Photos**, **Documents**, or **Music** lanes.
- Click **Options** on **Find duplicates** or **Advanced matching** to customize how files are matched (**Compare**) and where discarded duplicates go (**Duplicates:** **Move to Trash** default, **Move to a folder** / **MediaMango Quarantine**, or **Delete permanently** for photos/videos). Note: In File Manager, scanning always opens the side-by-side comparison review before any duplicate is removed.

4. Click **Review workflow** > **Start workflow**.

5. When duplicate groups are found, the **Duplicate Comparison Viewer** opens automatically:

- Inspect **Photo A / Photo B** (or **Video A / Video B**, **File A / File B**) side by side, or press **1** to keep A, **2** to keep B, **< / >** to switch groups, and **Space** for Quick Look.

- Or use the bottom bulk bar: set **For all groups** (for example **Keep largest file**, **Keep highest resolution**, **Keep oldest capture**, **Keep newest capture**, or **Keep clean filename (skip "Copy")**) and click **Apply to all groups**.
- Click **Done** in the top-right to finish review (any unreviewed groups are safely left untouched).

Recipe 5: Remove WhatsApp Clutter, Screenshots, Memes, and Greeting Cards

1. Go to **Home > File Manager**, import your folder, and click **Continue > Continue to actions**.
2. In **02 / Actions**, inside the **Photos** and/or **Videos** lane, click **+ Remove clutter** at the bottom of the lane.
3. Click **Options** on the **Remove clutter** row to choose which categories to flag:
 - **WhatsApp media** (IMG-YYYYMMDD-WA..., VID-YYYYMMDD-WA..., WhatsApp folder paths) — On by default.
 - **Memes & reaction images** — On by default.
 - **Greeting forwards** (good-morning/festival forward graphics) — On by default.
 - **Screenshots & screen recordings** — On by default.
 - **Chain messages & forwards** — On by default.
 - **Visual meme & card detection** — Optional; uses the local on-device CLIP vision model (~610 MB one-time download) to spot unlabelled memes and greeting cards visually.
 - **Keep likely important files** — On by default; protects camera originals with real lens EXIF, favourites, and large long-form videos.
 - **Matching sensitivity: Conservative (fewer false positives)** (default) or **Broader (catch more clutter)**.
4. Click **Review workflow > Start workflow**.
5. When the scan completes, the **Clutter review** dialog opens showing every candidate with its reason badge. Uncheck any file you want to keep, then click **Move selected to Trash** (or **Skip clutter removal**).

Recipe 6: Free Up Disk Space on Your Computer (Storage Analyser + Deep Cleanup)

1. **Clean system and app caches (Deep Cleanup):**
 - Go to **Home > Mango Tools > Deep Cleanup**.
 - In the startup prompt (**Save your work and close other apps**), close running browsers/creative apps and click **Apps closed — Scan** (or **Scan anyway**).
 - Browse the left category rail, expand any rule to inspect exact paths and risk notes, or click **Options > Safe caches only** in the bottom bar to select only low-risk cache items that rebuild automatically.
 - Click **Clean up** in the bottom-right and confirm the review dialog.
2. **Find and shrink or move the largest folders and files (Storage Analyser):**
 - Go to **Home > Mango Tools > Storage Analyser** and pick a folder or drive in the folder dialog.
 - Use **Visual Map** or **Tree & Map** to spot giant tiles, **File Types** to group by extension, or **Insights** to inspect **Compression Opportunities**, **Duplicate Folders**, **File Age Distribution**, and **Saved file findings (Scan for file findings)**.
 - Click tiles or rows to select them, then use the bottom bar to **Move to...** (**Choose folder...** or **Move to Trash**), **Copy to...**, or **Compress (Basic, Medium, Hard, Extreme, plus Photo format)**. Smaller verified outputs replace originals (moving the originals to Trash).

Recipe 7: Check Whether FLAC or WAV Files Are True Lossless (Lossless Music Checker)

1. Go to **Home > Mango Tools > Lossless Music Checker**.
2. In the native folder picker, select one or more music folders and confirm.

3. MediaMango decodes the audio tracks and analyses their high-frequency spectrum while showing progress on **Mango Tools**, then automatically opens the **Audio Lossless Check** report ([audio-results.html](#)).
4. In the report:
 - Filter tracks with the top pills: **All, Clean, Suspect, Errors**.
 - Click any track in the left list to view its **Measured frequency spectrum (kHz)**, **Verdict** (**Clean, Possible lossy source**, or **Error**), **Cutoff frequency**, **Codec**, **Sample rate**, and **Bit depth**.
 - Click **Show in Finder** / **Show in Explorer** to reveal a suspect file, or click **Save PDF** in the top bar to export a printable spectral audit report.

Recipe 8: Convert HEIC, RAW, MOV, WebP, AVIF, PNG, GIF, or WAV for Universal Compatibility

1. Press **Cmd+K** (macOS) or **Ctrl+K** (Windows/Linux) from any screen—or go to **Home > Mango Tools > Superuser**—type **convert**, and click **Open** on **Convert formats**.
2. In **Choose a folder**, drop a folder onto **Drop a folder here** or click **Choose folder...** (or pick a card under **Recent folders**).
3. On the **Convert Formats** screen:
 - **What to convert: All convertible files** (default — converts HEIC/RAW/PNG/WebP/AVIF > JPEG, MOV/GIF > MP4, WAV > FLAC), or pick a single pair (**HEIC > JPEG**, **MOV > MP4**, **RAW > JPEG**, **PNG > JPEG**, **WebP > JPEG**, **AVIF > JPEG**, **GIF > MP4**, **WAV > FLAC**).
 - **Originals: Keep originals in place** (default), **Replace originals (move to Trash)**, or **Move originals to “MediaMango Originals”**.
 - **Destination:** Leave as default (**MediaMango Converted beside your folder**) or click **Choose...** to pick a custom output folder.
4. Click **Preview** to inspect the exact conversion list, then click **Convert files**.

3. File Manager (Home > File Manager) — Complete Reference

File Manager ([cleanmango.html](#)) is MediaMango's unified batch workflow for **Photos, Videos, Documents, and Music**.

Stage 0: Folder Import ([cleanmango.html?surface=import](#))

- **Drop folders here / Choose Folders...:** Drag one or more folders onto the drop zone or click **Choose Folders...** to select multiple folders in the native dialog.
- When folders are staged:
 - **Add folders:** Append additional folders to the batch.
 - **Remove:** Remove an individual folder from the staged list.
 - **Continue:** Scans the staged folders and opens Step 01 / Choose files.
- **Protected paths:** System roots (**/**, **C:**, **/System**, **/Library**, **/Applications**, **C:\Windows**, **C:\Program Files**, **.app** bundles) are blocked from import so you cannot accidentally modify operating-system files.

Step 01 / Choose files

- **Default selection:** Every supported photo, video, document, and audio file in your imported folders starts **selected (checked) by default**.
- **Top toolbar controls:**
 - **Search... (#pipelineFileSearch):** Live filter by filename or relative path.
 - **+ Add folders:** Add more source folders without losing your current setup.
 - **Filters** dropdown (or category chips **All, Photos, Videos, Documents, Music**): Filter the visible file list by media category.
 - **Select** dropdown:
 - **Select all imported files:** Checks all imported files across all categories.
 - **Clear file selection:** Unchecks all files so you can select only specific categories or files.
 - **View toggle:** Switch between **List view** and **Grid view**.
 - **Change folders:** Return to the folder import screen to replace the folder list.
- **Bottom dock:** Shows the live selected count (for example **24 of 24 selected**) and the primary button **Continue to actions**.

Step 02 / Actions

Each media category that has at least one selected file displays an action lane card (**Photos, Videos, Documents, Music**).

- **Lane enable checkbox:** Uncheck **Enable Photos workflow**, **Enable Videos workflow**, **Enable Documents workflow**, or **Enable Music workflow** to skip that entire media category without changing your file selection.
- **Default steps in a new lane** (critical difference between Videos and other lanes):
 - **Photos lane default steps:** **1 Find duplicates**, **2 Advanced matching**, **3 Compress**.

- **Videos lane default steps:** 1 Find duplicates, 2 Advanced matching. (Compress is NOT added by default on new Videos lanes — click + Compress at the bottom of the Videos lane to add it.)
- **Documents lane default steps:** 1 Find duplicates, 2 Advanced matching, 3 Compress.
- **Music lane default steps:** 1 Find duplicates, 2 Advanced matching, 3 Compress.
- **Adding steps** (buttons at the bottom of each lane when a step is not yet in the lane):
 - + Find duplicates
 - + Advanced matching
 - + Remove clutter (available on **Photos** and **Videos** lanes)
 - + Compress
- **Removing a step:** Click ✕ (Remove <Step Name>) on the right side of any action row in a lane.
- **Configuring a step:** Click **Options** on any action row (or click the action row title) to expand its inline settings editor directly inside the lane.
- **Execution order:** When multiple steps are enabled in a lane, MediaMango prepares all duplicate/matching scans first (pausing for your interactive review only when actual duplicate groups or clutter candidates are found), and then runs **Compress** on the remaining selected files (excluding any files removed during duplicate or clutter review).
- **Bottom dock:** **Back to files** (left) and **Review workflow** (right).

Step 03 / Review

- Displays a plain-language execution plan for every enabled lane and step, including exact file counts, matching methods, compression codecs/presets, output folder names, and how original files will be handled.
- Shows a red warning banner only if an action is explicitly configured to permanently delete files.
- **Bottom dock:** **Back to actions** (left) and **Start workflow** (right).

4. Photos Options & Comparison Reference (**Photos** Lane)

Photos > Find duplicates (Options)

- **Compare** (`#dedupStrategySelect`):

- **Rapid Segment Hash** (`fast_hash`, default) — samples head, middle, and tail byte segments for fast duplicate detection.
- **Full Content (SHA-256)** (`exact_hash`) — byte-for-byte cryptographic verification of the entire file.
- **Size + Segment Hash** (`size_fast_hash`) — prefilters by exact byte size before hashing segments.
- **Size + Filename** (`size_name`) — matches files with identical byte size and filename.
- **Filename + EXIF** (`name_exif`) — matches filename together with embedded camera EXIF metadata.
- **Camera Metadata (EXIF)** (`metadata`) — matches capture timestamp and camera model.

- **Keep** (`#priorityRuleSelect`):

- **Review each group** (`select_each`, default)
- **Largest file** (`largest_size`)
- **Smallest file** (`smallest_size`)
- **Newest date** (`newest`)
- **Oldest date** (`oldest`)
- **Highest resolution** (`highest_resolution`)

- **Duplicates** (`#dedupActionSelect`):

- **Move to Trash** (`move_trash`, default) — moves rejected duplicates to the system Trash / Recycle Bin.
- **Move to a folder** (`move_duplicates_folder`) — reveals the **Folder** picker (**Choose...**, defaults to **MediaMango Quarantine** beside your folder).
- **Delete permanently** (`permanent_delete`) — permanently deletes rejected duplicates during review (cannot be undone).

- **More options:**

- **Minimum file size (KB)** (`#minSizeInput`, default 0) — skips files smaller than the specified size in KB.

Photos > Advanced matching (Options)

- Finds visually similar photos (resized copies, re-saved JPEGs, burst shots, or light crops) using 64-bit DCT perceptual hashing (**pHash**).

- **Similarity** (`#advSimilaritySelect`):

- **Balanced (8 <= bits)** (8, default) — catches re-compressed and resized copies with low false positives.
- **Exact Vision (0 bits)** (0) — nearly identical visual frames only.
- **Tight (4 <= bits)** (4) — minor edits or format changes.
- **Broad (12 <= bits)** (12) — wider visual similarity for burst/angle variations.

- **Keep** (`#advPriorityRuleSelect`): **Review each group** (default), **Highest resolution**, **Largest file**, **Smallest file**, **Newest date**, **Oldest date**.

- **Duplicates** (`#advDedupActionSelect`): **Move to Trash** (default), **Move to a folder** (**Choose...**, defaults to **MediaMango Quarantine**), **Delete permanently**.

Photos > Remove clutter (Options)

- **Categories to detect** (all checked by default except visual detection):
 - WhatsApp media
 - Memes & reaction images
 - Greeting forwards
 - Screenshots & screen recordings
 - Chain messages & forwards
- **Visual meme & card detection:** Optional checkbox (uses the local ~610 MB CLIP model when installed).
- **Keep likely important files:** Checked by default (protects camera EXIF originals and favourites).
- **Matching sensitivity:** **Conservative (fewer false positives)** (default) or **Broader (catch more clutter)**.
- **Review step:** Opens the **Clutter review** dialog after scanning so you can inspect every candidate and click **Move selected to Trash** or **Skip clutter removal**.

Photos > Compress (Options)

- **Preset pills:**
 - **Balanced** — HEIC, 85% quality, original dimensions. (Note: if you run a new Photos lane without opening presets, the initial lane default is JPEG at 84% quality; clicking **Balanced** switches to HEIC 85%.)
 - **Web & Social** — JPEG, 80% quality, **Resize dimensions** enabled at **1080p** (1920 × 1080).
 - **Smaller file** — AVIF, 65% quality, **Resize dimensions** enabled at **1080p** (1920 × 1080).
 - **Archival** — HEIC, 95% quality, original dimensions.
 - **Custom** — activates automatically when you adjust individual format, quality, or dimension controls.
- **Output format** cards:
 - **HEIC** (Recommended — High Efficiency, ~2× smaller than JPEG)
 - **JPEG** (Universal — compatible with every device, browser, and printer)
 - **AVIF** (Next-Gen — up to ~50% smaller than JPEG)
 - **PNG** (Lossless — best for screenshots, logos, and transparency)
- **Quality:**
 - Slider from **1%** to **100%** with live tier badge (**Maximum Fidelity**, **High Quality**, **Balanced**, **Compact**) and quick step chips: **Smaller (60%)**, **Balanced (75%)**, **High (85%)**, **Maximum (95%)**.
- **Dimensions:**
 - **Resize dimensions** toggle (`#resizeToggle`, Off by default).
 - When enabled, shows **Target scale** chips (**4K 3840 × 2160**, **QHD 2560 × 1440**, **1080p 1920 × 1080**, **720p 1280 × 720**, **Custom**), **Maximum size** (**Width × Height** in px), **Maintain aspect ratio** (On by default — never stretches images), and **Linear RGB gamma** (On by default — prevents dark halos when downscaling).
- **More options** (auto-expanded in File Manager):
 - **8-bit color quantization** (`#reducePalette`) — available when **PNG** is selected; shrinks PNGs by up to ~70%.
 - **Original files** (`#photoOriginalAction`):
 - **Keep in place (Recommended)** (`keep`, default) — writes optimised copies to **MediaMango Optimised** beside your folder and leaves originals untouched.
 - **Move to “MediaMango Originals”** (`move`) — writes optimised copies to **MediaMango Optimised** and moves the original files into **MediaMango Originals**.

- **Move originals to Trash (replace)** — writes optimised copies to **MediaMango Optimised** and moves the original files to the system Trash.
- **Test compression** button (**#sampleCompressBtn**): Encodes one sample photo and shows before/after byte savings with a **Reveal Sample** button.

5. Videos Options & Comparison Reference (**Videos** Lane)

Videos > Find duplicates & Advanced matching (Options)

- **Compare** (`#videoDedupMethodSelect`):
 - In **Find duplicates**: **Fast segment hash** (`hash_segments`, default) or **File size prefilter** (`size_compare`).
 - In **Advanced matching**: **Visual content similarity** (`content_compare`, default — extracts keyframes across each video clip and compares perceptual frame hashes to catch re-encoded or trimmed copies).
- **Keep** (`#videoPriorityRuleSelect`): **Review each group** (`select_each`, default), **Largest file**, **Smallest file**, **Newest date**, **Oldest date**.
- **Duplicates** (`#videoDedupActionSelect`):
 - **Move to Trash** (`move_trash`, default)
 - **Move to a folder** (`move_duplicates_folder` — opens **Folder** picker, defaults to **MediaMango Quarantine**)
 - **Delete permanently** (`permanent_delete`)

Videos > Remove clutter (Options)

- Same category checkboxes and sensitivity controls as **Photos > Remove clutter** (flags forwarded WhatsApp videos, screen recordings, and short meme clips for review in the **Clutter review** dialog).

Videos > Compress (Options)

Important: In File Manager (02 / Actions), new **Videos** lanes do not include **Compress** by default. Always click **+ Compress** at the bottom of the **Videos** lane first, then click **Options**.

- **Preset pills**:
 - **Balanced** (default) — **HEVC (H.265)**, **24 CRF**, **Original** resolution, **Keep original framerate**, **Convert to AAC Stereo (Recommended)** at **128 kbps (Balanced · Standard)**, **Medium (Recommended)** encoding speed.
 - **Web & Social** — **H.264 (AVC)**, **23 CRF**, **1080p** resolution, **Cap at 30 fps (Recommended for web)**, **Convert to AAC Stereo** at **128 kbps**, **Fast** encoding speed.
 - **Smaller file** — **AV1**, **30 CRF**, **720p** resolution, **Cap at 30 fps**, **Convert to AAC Stereo** at **96 kbps (Compact)**, **Medium** encoding speed.
 - **Archival** — **HEVC (H.265)**, **18 CRF**, **Original** resolution, **Keep original framerate**, **Pass-through (Copy original stream)** audio, **Slow (Maximum efficiency)** encoding speed.
 - **Custom** — selected automatically when you tweak individual controls below.
- **Codec** cards:
 - **HEVC (H.265)** (Recommended, default) — High Efficiency (~50% smaller than H.264 at the same visual quality).
 - **H.264 (AVC)** (Universal) — Maximum compatibility across all devices, browsers, and older TVs.
 - **AV1** (Next-Gen) — Royalty-free codec with the highest compression efficiency; slower software encoding when hardware AV1 encode is unavailable.
- **Quality**:
 - **Constant Rate Factor (CRF)** slider from **16** to **36** (default **24 CRF**; lower numbers mean higher visual quality and larger files) plus quick chips:
 - **Best (18 CRF** — Archival Fidelity)

- **High** (22 CRF — High Quality)
- **Balanced** (24 CRF — Balanced, default)
- **Smaller** (28 CRF — Compact)
- **Smallest** (32 CRF — Maximum Savings)
- **Resolution chips & Frame rate limit:**
 - **Resolution: Original** (default — never upscales; keeps source dimensions), **4K**, **1440p**, **1080p**, **720p**, **480p**.
 - **Frame rate limit** (#videoMaxFpsSelect):
 - **Keep original framerate** (0, default)
 - **Cap at 60 fps** (60)
 - **Cap at 30 fps (Recommended for web)** (30)
 - **Cap at 24 fps (Cinematic)** (24)
- **Audio:**
 - **Audio processing** (#videoAudioActionSelect):
 - **Convert to AAC Stereo (Recommended)** (aac, default)
 - **Pass-through (Copy original stream)** (copy)
 - **Mute (Strip audio track)** (mute)
 - **AAC Audio Bitrate** (#videoAudioBitrateSelect, shown when AAC is selected):
 - **64 kbps (Voice / Speech)** (64)
 - **96 kbps (Compact)** (96)
 - **128 kbps (Balanced · Standard)** (128, default)
 - **160 kbps (High Quality)** (160)
 - **192 kbps (Studio)** (192)
 - **256 kbps (Archival)** (256)
- **More options** (auto-expanded in File Manager):
 - **Hardware acceleration (GPU)** (#videoHwAccelToggle, **On** by default) — uses Apple VideoToolbox on macOS and NVENC / QSV / AMF on Windows/Linux when supported.
 - **Web streaming faststart** (#videoFastStartToggle, **On** by default) — moves the MP4 **moov** atom to the front so videos start playing immediately when streamed or shared.
 - **Strip private metadata** (#videoStripMetadataToggle, **Off** by default) — when turned On, strips embedded GPS coordinates, camera serial numbers, and creation timestamps.
 - **Encoding effort & speed** (#videoSpeedPresetSelect):
 - **Very Fast (Quick sharing)** (veryfast)
 - **Fast** (fast)
 - **Medium (Recommended)** (medium, default)
 - **Slow (Maximum efficiency)** (slow)
 - **Original files** (#videoOriginalAction):
 - **Keep in place (Recommended)** (keep, default) — writes compressed **.mp4** files to **MediaMango Compressed** beside your source folder and leaves originals untouched.
 - **Move to “MediaMango Originals”** (move) — writes compressed **.mp4** files to **MediaMango Compressed** and moves originals to **MediaMango Originals**.
 - **Move originals to Trash** (replace) — writes compressed **.mp4** files to **MediaMango Compressed** and moves originals to the system Trash.

- **Test 5s sample** button (**#sampleVideoCompressBtn**): Transcodes a 5-second sample of your first selected video and displays a **Reveal Sample** button so you can verify quality before running the batch.

6. Documents & Music Options Reference (Documents & Music Lanes)

Documents > Find duplicates & Advanced matching (Options)

- **Compare (#dedupMethodSelect):**
 - **Find duplicates** uses **Exact bytes** (**exact** — SHA-256 byte-for-byte match).
 - **Advanced matching** offers:
 - **Same page content** (**content**, default — matches PDFs with identical rendered page content even if metadata or file wrappers differ).
 - **Same extracted text** (**text** — matches documents whose normalized extracted text matches via SimHash/text comparison).
- **Keep (#priorityRuleSelect):** **Review each group** (**select_each**, default), **Oldest file**, **Newest file**, **Largest file**, **Smallest file**.
- **Duplicates (#dedupActionSelect):** **Move to Trash** (**move_trash**, default) or **Move to a folder** (**move_duplicates_folder**, defaults to **MediaMango Quarantine**).

Documents > Compress (Options)

- **PDF compression (#documentCompressPreset):**
 - **Balanced · 150 dpi** (**balanced**, default — GemaPDF level 6; strong size reduction for scanned and image-heavy PDFs while keeping text crisp).
 - **Low · 300 dpi** (**low** — GemaPDF level 3; gentle compression for print-quality PDFs).
 - **High · 72 dpi** (**high** — GemaPDF level 9; maximum size reduction for screen reading and email attachments).
 - **Advanced** (**custom** — reveals the **Image compression** slider from **1** to **9**, default **6 / 9**).
- **Originals (#documentOriginalAction):**
 - **Important default note:** In a new File Manager **Documents** lane, **Originals** defaults to **Replace (move to Trash)** (**replace**). If you want to keep your original PDFs/Office files untouched in place, open **Documents > Compress > Options** and change **Originals** to **Keep in place** (**keep**, which writes compressed copies to **MediaMango Compressed**) or **Move to “MediaMango Originals”** (**move**).
- **Safety guarantee:** Digitally signed or encrypted PDFs are automatically detected and skipped so signatures are never broken. Modern Office documents (**.docx**, **.xlsx**, **.pptx**) are losslessly repacked.

Music > Find duplicates & Advanced matching (Options)

- **Compare (#dedupMethodSelect):**
 - **Find duplicates** defaults to **Same song** (**same_song** — matches normalized Artist + Title + duration tags with acoustic verification) and also supports **Exact bytes** (**exact**) or **Same sound** (**acoustic**).
 - **Advanced matching** defaults to **Same sound** (**acoustic** — Chromaprint waveform acoustic fingerprinting that matches identical recordings across MP3, FLAC, AAC, WAV, or M4A even when tags or bitrates differ).
- **Keep (#priorityRuleSelect):** **Review each group** (**select_each**, default), **Oldest file**, **Newest file**, **Largest file**, **Smallest file**.
- **Duplicates (#dedupActionSelect):** **Move to Trash** (**move_trash**, default) or **Move to a folder** (**move_duplicates_folder**, defaults to **MediaMango Quarantine**).

Music > Compress (Options)

- **Format** (#audioCodecSelect):

- **Opus** • **smallest** (opus, default — .opus, highest perceptual quality at low bitrates)
- **AAC** • **compatible** (aac — .m4a, Apple/mobile standard)
- **MP3** • **universal** (mp3 — .mp3, plays on every car stereo and legacy player)
- **FLAC** • **lossless** (flac — .flac, bit-exact lossless compression for WAV/AIFF archives; hides the lossy **Bitrate** dropdown)

- **Bitrate** (#audioBitrateSelect, for Opus/AAC/MP3): **64 Kbps**, **96 Kbps**, **128 Kbps**, **160 Kbps**, **192 Kbps** (default), **256 Kbps**, **320 Kbps**.

- **Sample rate** (#audioSampleRateSelect): **Keep original** (default), **48 kHz**, **44.1 kHz**, **32 kHz**, **22.05 kHz**.

- **Channels** (#audioChannelsSelect): **Keep original** (default), **Mono**, **Stereo**.

- **Keep audio tags** (#audioPreserveMetadata, checked by default): Preserves ID3/Vorbis title, artist, album, and cover art tags.

- **Originals** (#audioOriginalAction): **Keep in place** (keep, default — writes output to **MediaMango Compressed**), **Replace (move to Trash)** (replace), **Move to “MediaMango Originals”** (move).

7. Duplicate Comparison Viewer (Side-by-Side Review)

Whenever **Find duplicates** or **Advanced matching** finds one or more duplicate groups, MediaMango opens the interactive **Duplicate Comparison Viewer**:

- **Left rail (Groups):**

- Lists every duplicate cluster (**Group 1**, **Group 2**, etc.) with item count and match badge.
- **Filter by name...** / **Filter by file name...**: Filter groups by filename.

- **Side-by-side comparison stage:**

- **Photos**: Shows **Photo A** and **Photo B** with resolution, byte size, capture date, camera model, and path. Click **Keep this photo** on either card (or press **1** for Photo A, **2** for Photo B, **< / >** to navigate groups, **Space** to toggle Quick Look).
- **Videos**: Shows **Video A** and **Video B** frame previews with codec, duration, resolution, and size. Click **Keep A** • **Resolve B** or **Keep B** • **Resolve A** (or press **1 / 2**).
- **Documents & Music**: Shows **File A** and **File B** (rendered PDF page preview, extracted text preview, or audio player + metadata). Includes **Fit width** and **Open file** buttons, plus **Keep A** • **Trash B** and **Keep B** • **Trash A** (label updates dynamically to **Archive** if **Move to a folder** was selected).

- **Bottom bulk bar (For all groups):**

- Choose a bulk rule from the **For all groups** dropdown:
- **Photos**: **Keep largest file**, **Keep smallest file**, **Keep highest resolution**, **Keep oldest capture**, **Keep newest capture**, **Keep clean filename** (skip "Copy").
- **Videos**: **Keep largest file**, **Keep smallest file**, **Keep oldest capture**, **Keep newest capture**, **Keep clean filename** (skip "Copy").
- **Documents / Music**: **Keep oldest file**, **Keep newest file**, **Keep largest file**, **Keep smallest file**, **Keep clean filename** (skip "Copy").
- Click **Apply to all groups** to resolve every remaining group at once using your chosen **Duplicates** disposal action (**Move to Trash**, **Move to a folder**, or **Delete permanently**).

- **Finishing review early**: Clicking **Done** in the top-right closes the viewer and continues the workflow; any groups you did not resolve are safely left untouched.

8. iPhone Photo Exporter (Home > Mango Tools > iPhone Photo Exporter)

Exports photos, videos, and Live Photos directly from a USB-connected iPhone or iPad ([iphone-export.html](#)) without iCloud or cloud uploads.

Connection & Automatic Scan

- Connect the iPhone/iPad with a USB cable, unlock the device, and tap **Trust** on **Trust This Computer?**.
- MediaMango detects the device automatically and scans the library. Use **Refresh** (or **Reload library**) to rescan, or the device dropdown ([#deviceSelect](#)) if multiple iOS devices are connected.

Step 01 / Choose media

- **Default selection:** All non-hidden photos and videos start selected by default.
- **Top filter bar:**
 - **Search name, place, album...** ([#searchInput](#)): Filter by filename, location, or album title.
 - **Media type** ([#kindSelect](#)): **All media** (default), **Photos**, **Videos**, **Live Photos**.
 - **Years** ([#yearSelect](#)): **All years** (default) or a specific capture year.
 - **Albums** ([#albumSelect](#)): **All albums** (default) or a specific iPhone album.
 - **Favourites** button ([#favoriteBtn](#)): Toggle filtering to favourite items only.
 - **More** menu: Contains **Include hidden items** ([#includeHiddenToggle](#), unchecked by default; enabling it includes the iPhone's Hidden album).
 - **Select** menu:
 - **Select all shown** ([#selectAllBtn](#)) — selects every item matching the current filters.
 - **Clear selection** ([#selectNoneBtn](#)) — deselects all items so you can filter to **Videos** (or **Photos**) and pick only what you want.
- **How selection interacts with filters:** Narrowing a filter scopes your selection to matching items; to export only videos, set **Media type** to **Videos** (or click **Select > Clear selection**, set **Media type** to **Videos**, and click **Select > Select all shown** or click individual cards).
- **Bottom dock:** Shows the selected item count and total size, plus the **Continue** button (advances to **02 / Choose folder**).

Step 02 / Choose folder

- **Save to:** Click **Choose folder...** ([#chooseFolderBtn](#)) to pick the destination folder on your computer.
- **Bottom dock:** **Back** (returns to **01 / Choose media**) and **Review import** (advances to **03 / Review**).

Step 03 / Review

- Shows the summary card (**Device**, **Selected**, **Destination**, **Existing files: Keep existing files and save new copies with a number** — MediaMango never overwrites existing files in the destination folder).
- **Copy options** disclosure (optional):
 - **Photo version** ([#versionSelect](#)):
 - **Edited image when available** (**current**, default)

- **Unmodified originals** (**original**)
- **Photo format** (**#formatPolicySelect**):
 - **Keep format (HEIC, JPEG, etc.)** (**preserve**, default)
 - **Convert to JPEG** (**jpeg** — converts exported HEIC photos to **.jpg** during export)
- **Bottom dock: Back** and **Import media** (**#exportBtn**).
- **During and after import:**
 - Shows a live progress bar with **Cancel**.
 - When complete, shows **Show export folder** (opens Finder / File Explorer) and **Done** (returns to **Mango Tools**).
 - **Safety:** Exporting is 100% read-only on the iPhone—nothing is ever deleted from the iPhone by MediaMango.

9. Storage Analyser (Home > Mango Tools > Storage Analyser)

Visualises disk usage and lets you move, copy, trash, or compress large folders and files in place ([storage.html](#)).

Launching & Top Toolbar

- Clicking **Storage Analyser** on **Mango Tools** opens a native folder picker immediately. Selecting a folder opens [storage.html](#) and scans the directory tree. (Storage Analyser never remembers previous folders across launches.)
- **Top bar:**
 - **Up arrow** (Cmd+↑ / Enclosing folder): Navigate up to the parent directory.
 - **Breadcrumbs:** Click any folder segment in the path bar to jump to that level.
 - **Open Folder...** (Cmd+O): Pick a different folder or drive to map.

5 Workbench View Tabs

1. **Visual Map:** Proportional squarified treemap tiles sized by byte usage and coloured by category (**Photos**, **Videos**, **Music**, **Documents**, **Archives**, **Other**). Click a tile to select it; double-click a folder tile to drill into it.
2. **Tree & Map:** Split view combining the collapsible **Folder Tree** on the left with the interactive **Visual Map** on the right.
3. **Folder Tree:** Hierarchical directory list sorted by byte size with percentage bars and item counts.
4. **File Types:** Aggregates every file by extension (such as **.mov**, **.mp4**, **.heic**, **.pdf**, **.zip**) showing total bytes, share of folder, and file count. Clicking an extension selects all matching files respecting active filters.
5. **Insights:**
 - **Compression Opportunities:** Highlights categories with estimated space savings and one-click compression buttons.
 - **Duplicate Folders:** Detects subfolders with identical contents.
 - **File Age Distribution:** Breakdown of bytes across age buckets.
 - **Saved file findings:** Click **Scan for file findings** (`#storageContentInsightsScanBtn`) to index the folder for exact duplicates, camera companions, and cleanup recommendations.

Filter Bar (Filters Button)

Click **Filters** in the workbench header to reveal:

- **Age** (`#storageAgeFilter`): **All ages** (default), **Last 7 days**, **Last 30 days**, **Last 3 months**, **Last year**, **Older than 1 year**.
- **Size** (`#storageSizeFilter`): **All sizes** (default), **Large (>100 MB)**, **Medium (10–100 MB)**, **Small (1–10 MB)**, **Tiny (<1 MB)**.
- **Category** (`#storageCategoryFilter`): **All categories** (default), **Photos**, **Videos**, **Music**, **Documents**, **Archives**, **Other**.
- **Search** (`#storageSearchInput`): **Search by name...**
- **Clear filters** (`#storageFilterClearBtn`): Resets all active filters.

Bottom Selection & Action Bar

- **Select All** (Cmd+A / Ctrl+A) and **Deselect** (Esc).
- When one or more files or folders are selected, the action bar reveals:
 - **Move to...** (#storageMoveBtn): Opens a menu with **Choose folder...** (relocates selected items to another folder) and **Move to Trash** (sends selected items to the system Trash; undoable via **History**).
 - **Copy to...** (#storageCopyBtn): Copies selected items to a chosen destination folder.
 - **Compress** (#storageCompressBtn): Opens the in-place storage compression menu for selected Photos, Videos, Music, and Documents:
 - **Photo format** (#storagePhotoFormatSelect, shown when photos are selected): **Auto** (default), **Lossless**, **AVIF**, **JPEG XL**, **WebP**, **JPEG**, **PNG**.
 - **Compression level** buttons: **Basic** (gentle, high fidelity), **Medium** (balanced everyday savings), **Hard** (aggressive size reduction), **Extreme** (maximum space reclamation).
 - **Safety**: Storage Analyser compression verifies each compressed output; only when the new file is smaller does it replace the original and move the original to the system Trash.
 - **Show in Finder** / **Show in Explorer** (#storageRevealBtn): Reveals the selected item in the OS file manager.
 - **Back to Mango Tools** (#nextBtn): Returns to **Mango Tools**.

10. Deep Cleanup / System Cleaner (Home > Mango Tools > Deep Cleanup)

Scans for reclaimable system, application, browser, creative-app, and developer caches ([system-cleaner.html](#)).

Scanning & Scope

- **Before scanning modal:** Prompts **Save your work and close other apps** with buttons **Apps closed — Scan** (recommended) and **Scan anyway**.
- **Scope:**
 - When opened directly from **Mango Tools**, performs a **Standard system scan** across safe user/system cache locations.
 - When opened with a folder handoff, scopes cleanup strictly to that folder.
- **Left category rail:** Groups findings by category (such as Application Caches, Browser Caches, Developer Tools, Creative App Caches, Logs & Diagnostics, Trash / Downloads).
- **Right detail pane:**
 - Category checkbox (**Select all** in category) and total reclaimable size.
 - Expandable rule rows showing exact file paths, item counts, byte totals, and safety explanations (whether caches rebuild automatically, require re-downloading assets, or move to Trash vs. permanent deletion).
- **Bottom action bar:**
 - **Rescan** ([#rescanBtn](#)): Runs a fresh scan.
 - **Options** ([#moreBtn](#)) menu:
 - **Safe caches only:** Automatically selects only low-risk cache rules that applications rebuild automatically.
 - **Clear selection:** Unchecks all rules.
 - **Show empty & unavailable:** Toggles visibility of rules with 0 bytes or unavailable providers.
 - **Clean up** ([#cleanBtn](#)): Opens a single-use confirmation dialog detailing whether selected items move to Trash or are permanently removed, then executes the cleanup.
- **Top header:** **History** button ([#historyBtn](#)) opens the **Cleaner history** dialog showing past cleanup runs; **Mango Tools** returns to the launcher.

11. Lossless Music Checker (Home > Mango Tools > Lossless Music Checker)

Verifies whether **.flac**, **.wav**, **.alac**, and **.aiff** files are genuine lossless recordings or upscaled transcodes from lossy MP3/AAC sources ([lossless.html](#) & [audio-results.html](#)).

- **How it launches:** Clicking **Lossless Music Checker** on **Mango Tools** opens a multi-folder picker immediately. After you choose one or more folders, MediaMango stays on **Mango Tools** while decoding the audio tracks and running FFT spectral cutoff analysis, then opens the **Audio Lossless Check** report ([audio-results.html](#)).
- **Audio Lossless Check Report ([audio-results.html](#)):**
 - **Summary strip:** Displays **Checked**, **Clean**, **Suspect**, and **Errors** counts.
 - **Filter pills:** **All**, **Clean**, **Suspect**, **Errors**.
 - **Track list (left pane):** Lists each file with its verdict pill (**Clean**, **Possible lossy source**, or **Error**) and detected cutoff kHz.
 - **Track detail (right pane):**
 - Displays **Verdict**, **Analysis summary**, **Cutoff frequency** (for example **16.0 kHz** indicating a 128 kbps MP3 transcode, vs. full spectrum up to **22.05 kHz**), **Codec**, **Sample rate**, **Bit depth**, and **Channels**.
 - Renders an interactive **Measured frequency spectrum (kHz)** canvas with a dashed cutoff marker line.
 - **Show in Finder / Show in Explorer ([#audioResultRevealBtn](#)):** Reveals the currently selected audio file on disk.
 - **Top bar actions:**
 - **Save PDF ([#exportAudioPdfBtn](#)):** Exports a multi-page PDF report with spectrograms and per-track verdicts.
 - **Back to Mango Tools:** Returns to **Mango Tools**.

12. Superuser (Cmd+K / Ctrl+K or Home > Mango Tools > Superuser)

Superuser ([superuser.html](#)) is MediaMango's command palette and power-user workbench. Press **Cmd+K** (macOS) or **Ctrl+K** (Windows/Linux) from any screen to open it (or focus its search box if already open).

Superuser Interface Controls

- **Search bar** (Search jobs..., `#superuserSearch`): Filter 100+ jobs by name, category, file format (**heic**, **mkv**, **flac**, **srt**), or keyword (**exif**, **gps**, **burst**, **shasum**, **clip**, **whisper**).
- **Folder bar**:
 - **Choose folder...** (`#superuserFolderBtn`) and **Clear** (`#superuserClearFolderBtn`): Pre-select a target folder before opening or running any job.
 - **Folder shortcuts** bar (appears as soon as a folder is selected):
 - **Reveal**: Open the folder in Finder / File Explorer.
 - **Treemap**: Open the folder directly in **Storage Analyser**.
 - **Clean Junk**: Preview and delete **.DS_Store**, **Thumbs.db**, **desktop.ini**, and **._*** AppleDouble files.
 - **Prune Empty**: Preview and remove empty subdirectories.
 - **Copy Path**: Copy the folder's absolute path to the clipboard.
 - **Copy CLI**: Copy an equivalent terminal command (**find**, **ffmpeg**, **exiftool**, **shasum**, or **mediamango run**) for the selected job.
- **Category filter chips**: **All**, **Folder operations**, **Media forensics**, **Structure & tidying**, **Extraction & media**, **Autosort**, **Photos**, **Videos**, **Music**, **Documents**, **Convert**, **Tools**, **FFmpeg**, **Text & AI**, **App**.

How Superuser Jobs Run

Each row in Superuser has an action button on the right:

1. Run / Configure (Engine Workbench Modal):

- Opens the **Superuser Engine Workbench** dialog (`#superuserModal`) directly on the Superuser page.
- Specify **Source paths — one per line** (or click **Choose files...** / **Choose folders...**), adjust any tool options, and click **Preview** (`#superuserEnginePreviewBtn`) to inspect affected files without changing anything.
- For file-changing jobs with a preview, MediaMango requires you to click **Preview** first; then click **Apply changes** (`#superuserModalRunBtn`). For file-changing jobs without a separate preview, check **I have reviewed the sources and settings and want to apply these changes** and click **Run operation**.
- Click **Copy results** (`#superuserEngineCopyBtn`) to copy the structured JSON/text output to the clipboard.

2. Open (Standalone Utility Workflows):

- Routes to the dedicated utility screen, carrying over your selected folder:
- **Photos / Videos / Documents / Music** rows in Superuser route to **File Manager** ([cleanmango.html?surface=import](#)), except **Lossless Checker** which opens [lossless.html](#).
- **Convert formats** opens [convert.html](#).
- **Camera ingest** opens [ingest.html](#).
- **Storage Analyser** opens [storage.html](#).

- **Flatten subfolders, Collect matching files, Collect by visual query, Quarantine WhatsApp, screenshots, memes, Resolve JPEG+RAW pairs, Resolve HEIC/JPEG/PNG/WebP copies, FFmpeg tools, Extract text, and Transcribe audio** open the corresponding tab in **Media Utilities** ([tools.html](#)).
- **Autosort files** opens [autosort.html](#).
- **Live Autosort & watch folders** opens [live-folders.html](#).

13. Standalone Utility Screens Reached from Superuser

Convert Formats (convert.html)

- **Sidebar tabs:** Choose folder > Convert Formats.
- **Controls:**
 - **What to convert** (`#convertPresetSelect`): All convertible files (default), HEIC > JPEG, MOV > MP4, RAW > JPEG, PNG > JPEG, WebP > JPEG, AVIF > JPEG, GIF > MP4, WAV > FLAC.
 - **Originals** (`#convertOriginalAction`): Keep originals in place (default), Replace originals (move to Trash), Move originals to “MediaMango Originals”.
 - **Destination:** Defaults to **MediaMango Converted** beside your folder (or click **Choose...** / **Default**).
 - **Buttons:** **Preview** (`#previewConvertBtn`) and **Convert files** (`#runConvertBtn`).

Camera / SD Card Ingest (ingest.html)

- **Sidebar tabs:** Camera / SD card > Preview & cull.
- **Step 1 (Camera / SD card):** Pick a mounted camera card from the volume grid, click **Choose folder...**, **Refresh**, or **Connect iPhone....**
- **Step 2 (Preview & cull):**
 - **Transfer** (`#ingestTransferMode`): Copy off the card (default) or Move off the card.
 - **Bursts** (`#ingestCullBursts`): Keep the last frame in each burst (default) or Keep every frame.
 - **File names** (`#ingestRenameKeepers`): Date, camera, and original number (default — e.g. 2024-11-05 Sony-A7IV 0412.jpg) or Keep camera names.
 - **Destination:** Defaults to **Pictures/MediaMango Ingest** (or click **Choose...** / **Default**).
 - **Already in library:** Click **Choose library...** to pick an existing Pictures folder and click **Match card** to skip shots already imported.
 - **Buttons:** **Preview** (`#previewIngestBtn`) and **Ingest** (`#runIngestBtn`).

Media Utilities (tools.html)

After selecting a folder on **Folder Import** (**Choose folder...**), six utility tabs unlock in the left sidebar:

1. Flatten Subfolders:

- **Protect programming projects** (`#flattenIgnoreProjects`, checked by default — skips directories containing .git, package.json, Cargo.toml, etc.).
- **Buttons:** **Preview Flatten** and **Flatten Files**.

2. Collect Media (Collect Matching Files):

- **Media Kind** (`#collectKind`): All media types, Photos only, Videos only, Music / Audio, Documents / PDFs.
- **Destination Folder Name** (`#collectDest`): Defaults to **Collected** inside the imported folder.
- **Visual Query (On-Device AI)** (`#collectVisual`): Natural-language CLIP search (e.g. photos of dogs, beach sunset, invoices). If the ~610 MB CLIP model is not yet installed, a **Download CLIP Model (~610 MB)** button appears.
- **Content Labels & Keywords** (`#collectLabels`): Match filenames/tags (e.g. whatsapp, screenshots, memes).

- Buttons: **Preview Collect** and **Collect Files**.

3. Quarantine Junk (Quarantine by Content):

- **Quarantine Keywords & Tags** (`#quarantineLabels`): Defaults to **whatsapp**, **screenshot**, **meme**. Moves matches into **MediaMango Quarantine** beside your folder.
- Buttons: **Preview Quarantine** and **Quarantine Files**.

4. Camera Pairs (Camera Pairs & Clones):

- **JPEG + RAW Companions: Pair Resolution Rule** (`#jpegRawKeep`) — **Keep RAW**, **trash JPEG companion** (default) or **Keep JPEG**, **trash RAW companion**. Buttons: **Preview JPEG+RAW** and **Resolve JPEG+RAW**.
- **Video Container Clones**: Detects identical video streams across **.mov**, **.mp4**, **.mkv**. Buttons: **Preview Containers** and **Keep Largest Copy**.

5. FFmpeg Tools:

- Writes outputs to **MediaMango Transcoded** beside your folder while leaving originals in place.
- **Media Utility** (`#ffmpegTool`) dropdown options:
 - **Extract audio track (Lossless AAC/MP3)** (`extract-audio`)
 - **Convert video to high-quality GIF** (`make-gif`)
 - **Trim video boundaries** (`trim-video` — start time & duration)
 - **Downscale video resolution (1080p / 720p)** (`downscale-video`)
 - **Mute / remove all audio tracks** (`mute-video`)
 - **Lossless container remux** (`remux-video` — e.g. MKV to MP4 without re-encoding)
 - **Change video playback speed** (`change-speed` — 0.5×, 1.5×, 2×, 4×)
 - **Deinterlace interlaced broadcast video** (`deinterlace-video` — BWDIF filter)
 - **Strip camera and GPS EXIF metadata** (`strip-metadata`)
 - **Normalize audio loudness (EBU R128)** (`normalize-audio`)
 - **Denoise audio (Speech clarity isolation)** (`denoise-audio`)
 - **Convert to 9:16 vertical short/reel** (`convert-aspect`)
- Buttons: **Preview Action** and **Run Tool**.

6. On-Device Text (On-Device Text & Transcription):

- Works on a single file without requiring a folder import.
- Click **Choose file...** (`#chooseTextFileBtn`), then click **Extract Text** (for PDF, DOCX, TXT, or image OCR) or **Transcribe Audio** (local **whisper-cli** speech-to-text), and click **Copy Text** to copy the output.

Autosort & Rename Files (autosort.html)

- **Import stage**: Drop folders or click **Choose Folders...** > **Continue**.
- **Organise your files (My categories)**:
 - **Flatten subfolders** checkbox (checked by default).
 - Add custom category folders (**+ Add category**) with a folder name and content description (uses local on-device AI components, ~610 MB one-time download if not yet installed).
 - Click **Sort files** in the bottom dock to preview suggested moves first, then confirm to move matched files into your category folders.
- **Review file names (Rename Files mode)**:
 - Previews content- and metadata-based filenames (document titles/headings, music tags, photo/video capture dates).

- Bottom dock buttons: **Refresh names** and **Rename files**.

Live Folders / Watched Folders (live-folders.html)

- Automates rules on folders while MediaMango is open.
- **Top toolbar:** **Add folder...** (`#addWatchFolderBtn`) and **Reload saved folders**.
- **Rule editor controls:**
 - **Run automatically:** **When files arrive**, **Every minute**, **Every 5 minutes** (default for new folders), **Every 15 minutes**, **Every 30 minutes**, **Every hour**, **Every day**, or custom **Interval in minutes (1–1440)**.
 - **Rules:** Click **Add rule** (or presets **JSON + installers**, **Images: memes / other**, **Import rules...**, **Export rules...**).
 - **Rule fields:** **Rule name (optional)**, **Rule status (On after saving / Off)**, **Look at (Files and folders, Files only, Folders only, Images, Videos, Audio, Documents)**, **Match (Every condition, At least one condition, None of these conditions)**.
 - **Conditions (When a file matches):** Match by filename, extension, file size in MB, modified/created age in days, folder item count, readable text, metadata field, JSON Pointer (`/project/name`), detected signal (**Meme, Screenshot, WhatsApp, Receipt, Academic, Work, Family**), or local CLIP **visual description**.
 - **Actions (Then do this):** **Sort into subfolder**, **Move to folder**, **Copy to folder**, **Rename**, **Move to Trash**, or **Show notification**, with collision policy **Rename incoming item** (default) or **Skip remaining actions**.
 - **Safe testing & saving:** Click **Test with a file...**, **Test with a folder...**, **Preview changes**, or **Check matching files** (none of these move files). Click **Save changes** (`#saveWatchFoldersBtn`) in the bottom footer to activate.

Custom Organisation Builder (Organisation in Superuser / Standalone Workspaces)

- Builds folder hierarchies and filenames by dragging or clicking token blocks across two lanes:
 - **Folder path** canvas (default tokens: **Year / Month name / Day (5th)**)
 - **File name** canvas (click **Use Date + camera + number** for `2024-11-05 Sony-A7IV 0412.jpg`, or leave empty to **Keep original names**)
- **57 supported tokens:**
 - **Calendar & Clock:** **Date**, **Time**, **Year**, **Month**, **Month name**, **Week**, **Day**, **Day (5th)**, **Day of week**, **Hour**, **Minute**, **Quarter**.
 - **Media & File:** **Media type**, **Orientation**, **Resolution**, **Duration**, **File size**, **Codec**, **Frame rate**, **HDR**, **Capture type**, **File type**, **Edit state**, **Original name**, **Original number**, **Sequence**.
 - **Camera, Music & Document Metadata:** **Camera model**, **Camera make**, **Lens**, **Artist**, **Album**, **Album artist**, **Composer**, **Genre**, **Track**, **Author**, **Title**, **Creator**, **Publisher**, **Series**, **Language**, **Page count**, **ISBN**, **DOI**, **Keywords**.
 - **Content, Place & Origin:** **Content category**, **Academic or personal**, **Work or personal**, **Location**, **City**, **Country**, **Download source**, **Saved by**, **Download date**, **Last used**, **Finder tag**.

14. Output Folders, Original-File Handling, and Undo (**History**)

Default Sibling Output Folders

When an operation creates new files or isolates files while keeping your source folder clean, MediaMango writes to a named folder right beside your imported folder:

- **MediaMango Optimised** — Photo compression output (**Photos > Compress**).
- **MediaMango Compressed** — Video, Document (when keeping originals), and Music compression output (**Videos / Documents / Music > Compress**).
- **MediaMango Converted** — Format conversion output (**Convert Formats**).
- **MediaMango Transcoded** — FFmpeg media tool output (**FFmpeg Tools**).
- **MediaMango Originals** — Archived source files when **Original files** is set to **Move to “MediaMango Originals”**.
- **MediaMango Quarantine** — Isolated duplicates, zero-byte files, corrupt files, or content-quarantined clutter.
- **Pictures/MediaMango Ingest** — Default destination for **Camera / SD Card Ingest**.

How Undo (**History** / **Cmd+Z** / **Ctrl+Z**) Works

- MediaMango records file moves, renames, conversions, compressions, and quarantine operations in a durable on-disk journal that **survives quitting and reopening the app**.
- To undo an operation:
 - Click **Undo** directly in the completion toast notification, **or**
 - Press **Cmd+Z** (macOS) / **Ctrl+Z** (Windows/Linux), **or**
 - Click **History** (clock icon in the top bar), switch to **All** or **Undoable**, and click **Undo** next to the operation.
- **What cannot be undone:**
 - Operations where you explicitly chose **Delete permanently** (and confirmed the permanent-deletion warning).
 - System Cleaner rules marked as permanent deletion, or files after you manually empty the macOS Trash / Windows Recycle Bin.

Complete Superuser catalog

This appendix contains all 232 current searchable catalog entries, generated directly from production exports. Search in Home > Mango Tools > Superuser, then use Open, Run or Configure as shown. Entries may open a separate utility or File Manager. Internal identifiers are reference keys, not terminal commands or chatbot access.

Read the controls correctly

Inspect means a read/analysis result rather than a requested source-file mutation; inspection can still write local indexes, samples or reports. Change means an operation can write or move files/settings. Destructive means removal or another consequential mutation. Preview/review bindings must be current. Actual runtime support, licensing, permissions and source formats still apply. Defaults below are the individual Superuser form's defaults; CleanMango and Storage can differ.

Disabled launcher entries

Autosort, Rename Files and Live Folders currently say Coming soon in Mango Tools. Related Superuser operations and retained utility destinations are listed here as advanced capabilities; do not imply those disabled buttons can be clicked. Prefer the practical chapters for normal routes.

Structured fields

Some tools expose JSON objects or review IDs. Do not invent opaque IDs, file snapshots or arbitrary JSON shapes. Obtain them through the corresponding current preview/result, or use a guided surface. Empty optional selections can mean the tool's whole source scope; explicitly verify scope before execution.

Catalog: Folder operations

Prune empty folders

Recursively remove empty subdirectories and folders containing only invisible OS junk like .DS_Store.

Location: Superuser > search "Prune empty folders"

Clean OS junk files

Delete invisible OS clutter like .DS_Store, Thumbs.db, desktop.ini, and AppleDouble ._ * resource forks.

Location: Superuser > search "Clean OS junk files"

Quarantine zero-byte files

Find empty 0-byte corrupt or interrupted files and safely isolate them into MediaMango Quarantine.

Location: Superuser > search "Quarantine zero-byte files"

Group loose files by extension

Tidy loose files in the folder into clean extension subdirectories like JPG, PNG, MP4, and PDF.

Location: Superuser > search "Group loose files by extension"

Sanitize cross-platform filenames

Fix invalid Windows, FAT32, and NAS characters (<, >, :, ", |, ?, *) and trim illegal trailing spaces or dots.

Location: Superuser > search "Sanitize cross-platform filenames"

Sync file dates to EXIF capture time

Update filesystem modified dates to match photos and videos real embedded EXIF capture times.

Location: Superuser > search "Sync file dates to EXIF capture time"

Generate SHA-256 checksum manifest

Create a standard checksums.sha256 manifest file for all files in the folder for integrity verification.

Location: Superuser > search "Generate SHA-256 checksum manifest"

Export folder inventory as CSV

Export a detailed spreadsheet listing every file, relative path, exact byte size, and modification date.

Location: Superuser > search "Export folder inventory as CSV"

Reveal folder in file manager

Open the chosen folder in Finder or File Explorer.

Location: Superuser > search "Reveal folder in file manager"

Catalog: Media forensics

Corrupt media doctor

Scan photos and videos for truncated streams, corrupt headers, or decoding failures and isolate them.

Location: Superuser > search "Corrupt media doctor"

Audit and strip GPS geotags

Inspect photos and videos for embedded GPS coordinates and location metadata, with 1-click privacy stripping.

Location: Superuser > search "Audit and strip GPS geotags"

Batch spectral lossless checker

Audit an entire music folder for fake FLAC and WAV files (lossy MP3 transcode upscales).

Location: Superuser > search "Batch spectral lossless checker"

Catalog: Structure & tidying

Build Year/Month dated hierarchy

Organize loose photos and videos into clean YYYY/YYYY-MM folders directly from embedded capture dates.

Location: Superuser > search "Build Year/Month dated hierarchy"

Unwrap single-child nested folders

Collapse redundant folder-in-folder extractions from zip archives and pull files to the parent directory.

Location: Superuser > search "Unwrap single-child nested folders"

Resolve duplicate filename collisions

Detect files sharing the same name across subfolders with different contents and disambiguate them.

Location: Superuser > search "Resolve duplicate filename collisions"

Run folder tidy recipe

One-click sequence: clean OS junk, prune empty folders, sanitize filenames, and sync EXIF timestamps.

Location: Superuser > search "Run folder tidy recipe"

Catalog: Extraction & media

Split Apple Live Photo pairs

Detect matching HEIC/JPEG stills and MOV companion video clips, with options to extract clips or keep stills.

Location: Superuser > search "Split Apple Live Photo pairs"

Extract embedded video subtitles

Extract embedded subtitle streams from MP4 and MKV video containers into standalone .srt files.

Location: Superuser > search "Extract embedded video subtitles"

Catalog: Autosort

Autosort files

Move loose files into Photos, Videos, Music, Documents, Archives, Apps, Code, Fonts, and Other. Album folders stay put; projects at the top move whole.

Location: Superuser > search "Autosort files" > linked utility (autosort.html?view=sort-view)

Linked settings: {"view": "sort-view"}

Catalog: Photos

Photo Deduplication

Find duplicate photos and review them side by side. Choose how files are matched on the next screen.

Location: Superuser > search "Photo Deduplication" > linked utility (cleanmango.html?surface=import)

Linked settings: {"view": "dedup-view"}

Advanced Photo Deduplication

Find near-duplicates with perceptual hashing — resized, recompressed, or lightly edited copies.

Location: Superuser > search "Advanced Photo Deduplication" > linked utility (cleanmango.html?surface=import)

Linked settings: {"view": "dedup-view", "submode": "advanced", "strategy": "phash"}

Photo Compression

Write smaller copies to MediaMango Optimised. Choose JPEG, AVIF, WebP, or PNG on the next screen.

Location: Superuser > search "Photo Compression" > linked utility (cleanmango.html?surface=import)

Linked settings: {"view": "optim-view"}

Photo Organisation

Build dated folders and shareable names such as 2024-11-05 Sony-A7IV 0412.jpg.

Location: Superuser > search "Photo Organisation" > linked utility (cleanmango.html?surface=import)

Linked settings: {"view": "organise-view"}

Catalog: Videos

Video Deduplication

Find duplicate clips. Choose segment hashes, visual similarity, or a size prefilter on the next screen.

Location: Superuser > search "Video Deduplication" > linked utility (cleanmango.html?surface=import)

Linked settings: {"view": "video-dedup-view"}

Video Compression

Write smaller MP4 copies to MediaMango Compressed. Choose H.264, HEVC, or AV1 on the next screen.

Location: Superuser > search "Video Compression" > linked utility (cleanmango.html?surface=import)

Linked settings: {"view": "video-compress-view"}

Video Organisation

Build folder trees and file names from capture date and camera metadata.

Location: Superuser > search "Video Organisation" > linked utility (cleanmango.html?surface=import)

Linked settings: {"view": "organise-view"}

Catalog: Documents

Document Deduplication

Match PDFs by page content, extracted text, or exact bytes. Choose the method on the next screen.

Location: Superuser > search "Document Deduplication" > linked utility (cleanmango.html?surface=import)

Linked settings: {"mode": "documents", "view": "dedup-view"}

Document Compression

Compress PDF images and repack modern Office files using the chosen original-file handling.

Location: Superuser > search "Document Compression" > linked utility (cleanmango.html?surface=import)

Linked settings: {"mode": "documents", "view": "compress-view"}

Document Organisation

Build folder trees from author, title, date, and other document tokens.

Location: Superuser > search "Document Organisation" > linked utility (cleanmango.html?surface=import)

Linked settings: {"mode": "documents", "view": "organise-view"}

Catalog: Music

Music Deduplication

Match tracks by exact bytes, tags, or acoustic fingerprint. Choose the method on the next screen.

Location: Superuser > search "Music Deduplication" > linked utility (cleanmango.html?surface=import)

Linked settings: {"mode": "music", "view": "dedup-view"}

Music Compression

Create smaller listening copies, or re-encode to FLAC. Choose Opus, AAC, MP3, or FLAC on the next screen.

Location: Superuser > search "Music Compression" > linked utility (cleanmango.html?surface=import)

Linked settings: {"mode": "music", "view": "compress-view"}

Lossless Checker

Decode FLAC/WAV and look for spectral cut-offs that suggest a prior lossy encode.

Location: Superuser > search "Lossless Checker" > linked utility (lossless.html)

Linked settings: {"mode": "music", "view": "lossless-view"}

Music Organisation

Build Artist/Album folder trees and rename from tags.

Location: Superuser > search "Music Organisation" > linked utility (cleanmango.html?surface=import)

Linked settings: {"mode": "music", "view": "organise-view"}

Catalog: Convert

Convert formats

Turn HEIC, RAW, PNG, WebP, AVIF, MOV, GIF, and WAV into everyday JPEG, MP4, or FLAC. Pick the conversion and what to do with originals on the next screen.

Location: Superuser > search "Convert formats" > linked utility (convert.html?view=convert-view)

Linked settings: {"view": "convert-view"}

Catalog: Camera ingest

Camera ingest

Preview a camera or SD card, cull bursts, and copy into a dated tree. Skip shots already in a library.

Location: Superuser > search "Camera ingest" > linked utility (ingest.html?view=ingest-view)

Linked settings: {"view": "ingest-view"}

Catalog: Storage

Storage Analyser

WinDirStat-style size map. Select tiles, then move, copy, compress, trash, or reveal in the file manager.

Location: Superuser > search "Storage Analyser" > linked utility (storage.html)

Catalog: Tools

Flatten subfolders

Move nested files up into the selected folder. Programming projects stay intact by default.

Location: Superuser > search "Flatten subfolders" > linked utility (tools.html?view=flatten-view)

Linked settings: {"view": "flatten-view"}

Collect matching files

Gather photos, videos, music, or documents into one folder. Choose the kind on the next screen.

Location: Superuser > search "Collect matching files" > linked utility (tools.html?view=collect-view)

Linked settings: {"view": "collect-view"}

Collect by visual query

On-device CLIP search: photos of dogs, beach sunset, and similar queries.

Location: Superuser > search "Collect by visual query" > linked utility (tools.html?view=collect-view)

Linked settings: {"view": "collect-view"}

Download CLIP visual search

Install the on-device CLIP model (~610 MB) for visual collect.

Location: Superuser > search "Download CLIP visual search" > linked utility (tools.html?view=collect-view)

Linked settings: {"view": "collect-view"}

Quarantine WhatsApp, screenshots, memes

Move labelled clutter into MediaMango Quarantine beside the folder.

Location: Superuser > search "Quarantine WhatsApp, screenshots, memes" > linked utility (tools.html?view=quarantine-view)

Linked settings: {"view": "quarantine-view"}

Resolve JPEG+RAW pairs

Keep RAW and trash the JPEG companion, or the reverse. Choose which to keep on the next screen.

Location: Superuser > search "Resolve JPEG+RAW pairs" > linked utility (tools.html?view=pairs-view)

Linked settings: {"view": "pairs-view"}

Resolve HEIC/JPEG/PNG/WebP copies

Same-shot container copies: keep the largest file.

Location: Superuser > search "Resolve HEIC/JPEG/PNG/WebP copies" > linked utility (tools.html?view=pairs-view)

Linked settings: {"view": "pairs-view"}

Catalog: FFmpeg tools

Extract audio

Pull an MP3 from video files. Copies land in MediaMango Transcoded.

Location: Superuser > search "Extract audio" > linked utility (tools.html?view=ffmpeg-view&tool=extract-audio)

Linked settings: {"view": "ffmpeg-view", "tool": "extract-audio"}

Mute video

Remove the audio track from video files.

Location: Superuser > search "Mute video" > linked utility (tools.html?view=ffmpeg-view&tool=mute-video)

Linked settings: {"view": "ffmpeg-view", "tool": "mute-video"}

Remux video

Losslessly remux containers, for example MKV to MP4.

Location: Superuser > search "Remux video" > linked utility (tools.html?view=ffmpeg-view&tool=remux-video)

Linked settings: {"view": "ffmpeg-view", "tool": "remux-video"}

Trim video

Cut a clip to a start time and duration.

Location: Superuser > search "Trim video" > linked utility (tools.html?view=ffmpeg-view&tool=trim-video)

Linked settings: {"view": "ffmpeg-view", "tool": "trim-video"}

Make GIF

Convert video to an animated GIF.

Location: Superuser > search "Make GIF" > linked utility (tools.html?view=ffmpeg-view&tool=make-gif)

Linked settings: {"view": "ffmpeg-view", "tool": "make-gif"}

Downscale video

Reduce resolution to 1080p or 720p without the full compression pipeline.

Location: Superuser > search "Downscale video" > linked utility (tools.html?view=ffmpeg-view&tool=downscale-video)

Linked settings: {"view": "ffmpeg-view", "tool": "downscale-video"}

Change speed

Speed up or slow down video (2× or 0.5×).

Location: Superuser > search "Change speed" > linked utility (tools.html?view=ffmpeg-view&tool=change-speed)

Linked settings: {"view": "ffmpeg-view", "tool": "change-speed"}

Deinterlace video

Deinterlace vintage or interlaced footage with BWDIF.

Location: Superuser > search "Deinterlace video" > linked utility (tools.html?view=ffmpeg-view&tool=deinterlace-video)

Linked settings: {"view": "ffmpeg-view", "tool": "deinterlace-video"}

Strip metadata

Remove EXIF, GPS, and camera metadata for privacy.

Location: Superuser > search "Strip metadata" > linked utility (tools.html?view=ffmpeg-view&tool=strip-metadata)

Linked settings: {"view": "ffmpeg-view", "tool": "strip-metadata"}

Normalize audio

Loudness-normalise audio with EBU R128.

Location: Superuser > search "Normalize audio" > linked utility (tools.html?view=ffmpeg-view&tool=normalize-audio)

Linked settings: {"view": "ffmpeg-view", "tool": "normalize-audio"}

Denoise audio

Remove background noise and hiss from recordings.

Location: Superuser > search "Denoise audio" > linked utility (tools.html?view=ffmpeg-view&tool=denoise-audio)

Linked settings: {"view": "ffmpeg-view", "tool": "denoise-audio"}

Convert to 9:16 vertical

Reframe video for Reels and Shorts.

Location: Superuser > search "Convert to 9:16 vertical" > linked utility (tools.html?view=ffmpeg-view&tool=convert-aspect)

Linked settings: {"view": "ffmpeg-view", "tool": "convert-aspect"}

Catalog: On-device text

Extract text

Extract PDF, DOCX, or OCR text from a file.

Location: Superuser > search "Extract text" > linked utility (tools.html?view=text-view)

Linked settings: {"view": "text-view"}

Transcribe audio

Transcribe with whisper-cli if it is installed on this computer.

Location: Superuser > search "Transcribe audio" > linked utility (tools.html?view=text-view)

Linked settings: {"view": "text-view"}

Catalog: App

Mango Tools

Open the directory of cleanup, inspection and automation tools.

Location: Superuser > search "Mango Tools" > linked utility (mango-tools.html)

Settings

Folder import preferences, updates, licensing and support links.

Location: Superuser > search "Settings"

Switch appearance

Toggle light and dark mode.

Location: Superuser > search "Switch appearance"

Action history

Review recent jobs and undo when a reverse operation exists.

Location: Superuser > search "Action history"

Undo last file operation

Reverse the last undoable move, organisation, Autosort, convert, or ingest.

Location: Superuser > search "Undo last file operation"

Live Autosort & watch folders

Watch folders and choose automatic sorting or change notifications.

Location: Superuser > search "Live Autosort & watch folders" > linked utility (live-folders.html)

MediaMango Guide

Open the MediaMango Guide on the website.

Location: Superuser > search "MediaMango Guide"

Check for updates

Open the MediaMango website for the latest build.

Location: Superuser > search "Check for updates"

Privacy Policy & Terms

Open the privacy policy and terms of service.

Location: Superuser > search "Privacy Policy & Terms"

Plan & licence

View plan, trial, or upgrade options.

Location: Superuser > search "Plan & licence"

Catalog: Matching algorithms

Match against a protected library

Return source-bound review groups; reference files are protected during reviewed resolution.

Location: Superuser > search "Match against a protected library"

Operation: scan_media_matches. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: **File type:** Photos; Videos; Music; Documents (default photo) / **Matching method** (default exact) / **Protected reference paths:** json (default []) / **Exact file selection (optional):** json / **Video settings:** json (default {})

Plan bulk keep decisions

Choose keepers inside a current review, always retaining protected reference files.

Location: Superuser > search "Plan bulk keep decisions"

Operation: plan_matching_selection. Behavior: inspect. Source scope: none. Review evidence is required before resolving candidates.

Controls: Matching review ID / **Keep rule:** largest_size; smallest_size; newest; oldest; highest_resolution; shortest_path; preferred_path (default largest_size) / **Preferred folder:** path [optional]

Photos: camera metadata match

Compare capture metadata and file evidence. Returns review groups without removing files.

Location: Superuser > search "Photos: camera metadata match"

Operation: run_photo_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Minimum file size (KB): 0-100000000 (default 0) / **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "metadata"}

Photos: size and filename match

Find matching names and sizes without hashing every file. Returns review groups without removing files.

Location: Superuser > search "Photos: size and filename match"

Operation: run_photo_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Minimum file size (KB): 0-100000000 (default 0) / **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "size_name"}

Photos: size-prefiltered segment hash

Prefilter equal sizes before checking selected byte segments. Returns review groups without removing files.

Location: Superuser > search "Photos: size-prefiltered segment hash"

Operation: run_photo_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Minimum file size (KB): 0-100000000 (default 0) / **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "size_fast_hash"}

Photos: rapid segment hash

Compare sampled file segments. Returns review groups without removing files.

Location: Superuser > search "Photos: rapid segment hash"

Operation: run_photo_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Minimum file size (KB): 0-100000000 (default 0) / **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "fast_hash"}

Photos: full content hash

Compare complete file hashes. Returns review groups without removing files.

Location: Superuser > search "Photos: full content hash"

Operation: run_photo_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Minimum file size (KB): 0-100000000 (default 0) / **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "exact_hash"}

Photos: filename and EXIF match

Compare filenames with embedded camera metadata. Returns review groups without removing files.

Location: Superuser > search "Photos: filename and EXIF match"

Operation: run_photo_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: **Minimum file size (KB):** 0-100000000 (default 0) / **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "name_exif"}

Photos: perceptual DCT hash

Find visually similar photos using the shared RustDCT pHash. Returns review groups without removing files.

Location: Superuser > search "Photos: perceptual DCT hash"

Operation: run_photo_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: **Minimum file size (KB):** 0-100000000 (default 0) / **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "phash"}

Videos: Fast segment match

Scan video matches and inspect every returned group before any removal.

Location: Superuser > search "Videos: Fast segment match"

Operation: run_video_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "hash_segments"}

Videos: Size prefilter

Scan video matches and inspect every returned group before any removal.

Location: Superuser > search "Videos: Size prefilter"

Operation: run_video_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "size_compare"}

Videos: Visual content similarity

Scan video matches and inspect every returned group before any removal.

Location: Superuser > search "Videos: Visual content similarity"

Operation: run_video_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: **Exact file selection (optional):** json / **Window matching settings:** json (default {})

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "method": "content_compare"}

Documents: Exact bytes

Run the existing matching method and return its review groups without changing files.

Location: Superuser > search "Documents: Exact bytes"

Operation: run_library_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: **Exact file selection (optional):** json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "mediaKind": "document", "method": "exact"}

Documents: Document content

Run the existing matching method and return its review groups without changing files.

Location: Superuser > search "Documents: Document content"

Operation: run_library_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Exact file selection (optional): json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "mediaKind": "document", "method": "content"}

Documents: Normalized extracted text

Run the existing matching method and return its review groups without changing files.

Location: Superuser > search "Documents: Normalized extracted text"

Operation: run_library_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Exact file selection (optional): json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "mediaKind": "document", "method": "text"}

Music: Exact bytes

Run the existing matching method and return its review groups without changing files.

Location: Superuser > search "Music: Exact bytes"

Operation: run_library_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Exact file selection (optional): json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "mediaKind": "audio", "method": "exact"}

Music: Content hash

Run the existing matching method and return its review groups without changing files.

Location: Superuser > search "Music: Content hash"

Operation: run_library_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Exact file selection (optional): json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "mediaKind": "audio", "method": "content"}

Music: Text / metadata evidence

Run the existing matching method and return its review groups without changing files.

Location: Superuser > search "Music: Text / metadata evidence"

Operation: run_library_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Exact file selection (optional): json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "mediaKind": "audio", "method": "text"}

Music: Song tags with acoustic fallback

Run the existing matching method and return its review groups without changing files.

Location: Superuser > search "Music: Song tags with acoustic fallback"

Operation: run_library_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Exact file selection (optional): json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "mediaKind": "audio", "method": "same_song"}

Music: Chromaprint recording match

Run the existing matching method and return its review groups without changing files.

Location: Superuser > search "Music: Chromaprint recording match"

Operation: run_library_dedup. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Exact file selection (optional): json

Fixed engine settings: {"priorityRule": "select_each", "actionStrategy": "move_trash", "archivePath": "", "mediaKind": "audio", "method": "acoustic"}

Photo content suggestions

Inspect exact, visual or text candidates, keeper evidence, and scan limits.

Location: Superuser > search "Photo content suggestions"

Operation: preview_cleanmango_content. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Exact file selection (optional): json

Fixed engine settings: {"mediaKind": "photo", "selection": {"mode": "all"}}

Document content suggestions

Inspect exact, visual or text candidates, keeper evidence, and scan limits.

Location: Superuser > search "Document content suggestions"

Operation: preview_cleanmango_content. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: Exact file selection (optional): json

Fixed engine settings: {"mediaKind": "document", "selection": {"mode": "all"}}

Catalog: Reviewed file changes

Apply matching review decisions

Validate current file evidence and protected references before moving reviewed files to Trash or quarantine.

Location: Superuser > search "Apply matching review decisions"

Operation: resolve_matching_review. Behavior: destructive. Source scope: none.

Controls: Matching review ID / Files to keep: json (default []) / **Files to discard:** json (default []) / **Discarded files:** move_trash; move_duplicates_folder (default move_trash)

Apply selected diagnostic candidates

Apply only explicitly selected confirmed candidates from an unexpired diagnostic review.

Location: Superuser > search "Apply selected diagnostic candidates"

Operation: run_file_diagnostics. Behavior: change. Source scope: none.

Controls: **Diagnostic review ID** / **Selected candidate paths:** json (default [])

Resolve one explicit keep/discard pair

Apply an explicit file decision. Source existence and keep/discard overlap are checked by the existing resolver.

Location: Superuser > search "Resolve one explicit keep/discard pair"

Operation: resolve_manual_conflict. Behavior: destructive. Source scope: none.

Controls: **File to keep:** path / **File to discard:** path / **Discarded files:** Move to Trash; Move to quarantine; Permanently delete (default move_trash) / **Quarantine folder (optional)** / **Comparison type:** photo; video; document; audio (default photo)

Resolve explicit keep/discard lists

Apply explicit file decisions through the shared batch resolver.

Location: Superuser > search "Resolve explicit keep/discard lists"

Operation: resolve_manual_conflicts. Behavior: destructive. Source scope: none.

Controls: **Files to keep:** paths / **Files to discard:** paths / **Discarded files:** Move to Trash; Move to quarantine; Permanently delete (default move_trash) / **Quarantine folder (optional)** / **Comparison type:** photo; video; document; audio (default photo)

Resolve a content-matching snapshot

Apply a reviewed photo/document group using its original file snapshots; stale evidence is rejected.

Location: Superuser > search "Resolve a content-matching snapshot"

Operation: resolve_cleanmango_match. Behavior: destructive. Source scope: none.

Controls: **Reviewed ContentFile snapshots:** json (default []) / **File to keep:** path / **File type:** photo; document (default photo)

Remove reviewed clutter snapshots

Move explicitly selected clutter candidates to Trash after scope and source-snapshot checks.

Location: Superuser > search "Remove reviewed clutter snapshots"

Operation: resolve_cleanmango_clutter. Behavior: destructive. Source scope: paths.

Controls: **File type:** photo; video; document (default photo) / **Source selection:** json (default {"mode": "all"}) / **Selected ContentFile snapshots:** json (default [])

Catalog: Content detection

Photo clutter detection

Inspect filename, text and optional visual clutter evidence; candidates are never removed by this scan.

Location: Superuser > search "Photo clutter detection"

Operation: preview_cleanmango_clutter. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: **WhatsApp files** (default On) / **Memes and stickers** (default On) / **Greeting cards** (default On) / **Screenshots** (default On) / **Forwarded chain messages** (default On) / **Use installed CLIP model** (default Off) / **Protect important files** (default On) / **Sensitivity:** conservative; broader (default conservative) / **Exact file selection (optional):** json

Fixed engine settings: {"mediaKind": "photo", "selection": {"mode": "all"}}

Video clutter detection

Inspect filename, text and optional visual clutter evidence; candidates are never removed by this scan.

Location: Superuser > search "Video clutter detection"

Operation: preview_cleanmango_clutter. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: WhatsApp files (default On) / Memes and stickers (default On) / Greeting cards (default On) / Screenshots (default On) / Forwarded chain messages (default On) / Use installed CLIP model (default Off) / Protect important files (default On) / Sensitivity: conservative; broader (default conservative) / Exact file selection (optional): json

Fixed engine settings: {"mediaKind": "video", "selection": {"mode": "all"}}

Document clutter detection

Inspect filename, text and optional visual clutter evidence; candidates are never removed by this scan.

Location: Superuser > search "Document clutter detection"

Operation: preview_cleanmango_clutter. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: WhatsApp files (default On) / Memes and stickers (default On) / Greeting cards (default On) / Screenshots (default On) / Forwarded chain messages (default On) / Use installed CLIP model (default Off) / Protect important files (default On) / Sensitivity: conservative; broader (default conservative) / Exact file selection (optional): json

Fixed engine settings: {"mediaKind": "document", "selection": {"mode": "all"}}

Collect by type, label or visual query

Gather matching files using file type, content classification and optional local CLIP search.

Location: Superuser > search "Collect by type, label or visual query"

Operation: run_collect_job. Behavior: change. Source scope: paths. Preview: preview_collect_job.

Controls: File type: all; photo; video; audio; document (default all) / Destination folder: path [optional] / Visual query (optional) / Content labels (comma-separated, optional)

Quarantine by content labels

Inspect content-matched clutter before moving it to MediaMango Quarantine.

Location: Superuser > search "Quarantine by content labels"

Operation: run_quarantine_job. Behavior: change. Source scope: paths. Preview: preview_quarantine_job.

Controls: Content labels (default whatsapp,screenshot,meme)

Catalog: Encoding engines

Test photo encoding

Encode one sample with libvips and compare sizes without replacing the original.

Location: Superuser > search "Test photo encoding"

Operation: run_photo_sample_compress. Behavior: inspect. Source scope: paths.

Controls: Output format: jpeg; webp; avif; png (default webp) / Quality: 1-100 (default 85) / Reduce PNG / WebP palette (default Off) / Resize photos (default Off) / Width (pixels): 1-65535 (default 1920) / Height (pixels): 1-65535 (default 1080) / Keep aspect ratio (default On) / Resize in linear light (default On) / Exact file selection (optional): json

Fixed engine settings: {"resizeMethod": "lanczos3"}

Encode and resize photos

JPEG, WebP, AVIF and PNG with palette reduction, orientation and linear-light resizing.

Location: Superuser > search "Encode and resize photos"

Operation: run_photo_pipeline. Behavior: change. Source scope: paths.

Controls: **Output format:** jpeg; webp; avif; png (default webp) / **Quality:** 1-100 (default 85) / **Reduce PNG / WebP palette** (default Off) / **Resize photos** (default Off) / **Width (pixels):** 1-65535 (default 1920) / **Height (pixels):** 1-65535 (default 1080) / **Keep aspect ratio** (default On) / **Resize in linear light** (default On) / **Exact file selection (optional):** json / **Original files:** Keep originals; Archive originals; Replace originals (default keep)

Fixed engine settings: {"resizeMethod": "lanczos3"}

Test PDF compression

Preview GemaPDF compression, image deduplication and metadata handling on one PDF. Signed documents stay intact.

Location: Superuser > search "Test PDF compression"

Operation: preview_document_compress. Behavior: inspect. Source scope: paths.

Controls: **Compression strength:** 1-9 (default 6) / **Recompress PDF streams** (default On) / **Deduplicate PDF images** (default On) / **Remove document metadata** (default Off) / **Exact file selection (optional):** json

Compress PDFs and Office files

Run the shared document engine with every currently exposed PDF control.

Location: Superuser > search "Compress PDFs and Office files"

Operation: run_document_compress. Behavior: change. Source scope: paths.

Controls: **Compression strength:** 1-9 (default 6) / **Recompress PDF streams** (default On) / **Deduplicate PDF images** (default On) / **Remove document metadata** (default Off) / **Exact file selection (optional):** json / **Original files:** Keep originals; Archive originals; Replace originals; Move originals to Trash (default keep)

Encode music with full controls

Choose codec, bitrate, sample rate, mono/stereo, tags and original-file handling.

Location: Superuser > search "Encode music with full controls"

Operation: run_audio_compress. Behavior: change. Source scope: paths.

Controls: **Codec:** opus; aac; mp3; flac (default opus) / **Bitrate (kbps):** 32-512 (default 192) / **Sample rate:** Keep source; 22,050 Hz; 32,000 Hz; 44,100 Hz; 48,000 Hz / **Channels:** Keep source; Mono; Stereo / **Keep metadata** (default On) / **Original files:** Keep originals; Archive originals; Replace originals (default keep) / **Exact file selection (optional):** json

Estimate video compression

Inspect or configure codec, quality, dimensions, frame rate, audio, encoder speed, metadata and hardware acceleration.

Location: Superuser > search "Estimate video compression"

Operation: estimate_video_compress. Behavior: inspect. Source scope: paths.

Controls: **Video codec:** H.264; HEVC; AV1 (default compatible) / **CRF quality:** 0-63 (default 22) / **Maximum height (pixels or original)** (default original) / **Maximum frames per second (0 keeps source):** 0-120 (default 0) / **Audio:** Encode AAC; Copy audio; Remove audio (default aac) / **Audio bitrate (kbps):** 32-512 (default 128) / **Encoder speed preset** (default medium) / **Fast-start streaming** (default On) / **Remove metadata** (default Off) / **Use available hardware encoding** (default On) / **Exact file selection (optional):** json / **Original files:** Keep originals; Archive originals; Replace originals (default keep)

Test a video sample

Inspect or configure codec, quality, dimensions, frame rate, audio, encoder speed, metadata and hardware acceleration.

Location: Superuser > search "Test a video sample"

Operation: run_video_sample_compress. Behavior: inspect. Source scope: paths.

Controls: **Video codec:** H.264; HEVC; AV1 (default compatible) / **CRF quality:** 0-63 (default 22) / **Maximum height (pixels or original)** (default original) / **Maximum frames per second (0 keeps source):** 0-120 (default 0) / **Audio:** Encode AAC; Copy audio; Remove audio (default aac) / **Audio bitrate (kbps):** 32-512 (default 128) / **Encoder speed preset** (default medium) / **Fast-start streaming** (default On) / **Remove metadata** (default Off) / **Use available hardware encoding** (default On) / **Exact file selection (optional):** json / **Original files:** Keep originals; Archive originals; Replace originals (default keep)

Encode videos with full controls

Inspect or configure codec, quality, dimensions, frame rate, audio, encoder speed, metadata and hardware acceleration.

Location: Superuser > search "Encode videos with full controls"

Operation: run_video_compress. Behavior: change. Source scope: paths.

Controls: **Video codec:** H.264; HEVC; AV1 (default compatible) / **CRF quality:** 0-63 (default 22) / **Maximum height (pixels or original)** (default original) / **Maximum frames per second (0 keeps source):** 0-120 (default 0) / **Audio:** Encode AAC; Copy audio; Remove audio (default aac) / **Audio bitrate (kbps):** 32-512 (default 128) / **Encoder speed preset** (default medium) / **Fast-start streaming** (default On) / **Remove metadata** (default Off) / **Use available hardware encoding** (default On) / **Exact file selection (optional):** json / **Original files:** Keep originals; Archive originals; Replace originals (default keep)

Catalog: Format conversions

HEIC to JPEG

Preview matching inputs, then convert with explicit original-file handling.

Location: Superuser > search "HEIC to JPEG"

Operation: run_conversion. Behavior: change. Source scope: paths. Preview: preview_conversion.

Controls: **Original files:** Keep originals; Archive originals; Replace originals (default keep)

Fixed engine settings: {"preset": "heic_jpeg"}

MOV to MP4

Preview matching inputs, then convert with explicit original-file handling.

Location: Superuser > search "MOV to MP4"

Operation: run_conversion. Behavior: change. Source scope: paths. Preview: preview_conversion.

Controls: **Original files:** Keep originals; Archive originals; Replace originals (default keep)

Fixed engine settings: {"preset": "mov_mp4"}

RAW to JPEG

Preview matching inputs, then convert with explicit original-file handling.

Location: Superuser > search "RAW to JPEG"

Operation: run_conversion. Behavior: change. Source scope: paths. Preview: preview_conversion.

Controls: **Original files:** Keep originals; Archive originals; Replace originals (default keep)

Fixed engine settings: {"preset": "raw_jpeg"}

PNG to JPEG

Preview matching inputs, then convert with explicit original-file handling.

Location: Superuser > search "PNG to JPEG"

Operation: run_conversion. Behavior: change. Source scope: paths. Preview: preview_conversion.

Controls: **Original files:** Keep originals; Archive originals; Replace originals (default keep)

Fixed engine settings: {"preset": "png_jpeg"}

WebP to JPEG

Preview matching inputs, then convert with explicit original-file handling.

Location: Superuser > search "WebP to JPEG"

Operation: run_conversion. Behavior: change. Source scope: paths. Preview: preview_conversion.

Controls: Original files: Keep originals; Archive originals; Replace originals (default keep)

Fixed engine settings: {"preset": "webp_jpeg"}

AVIF to JPEG

Preview matching inputs, then convert with explicit original-file handling.

Location: Superuser > search "AVIF to JPEG"

Operation: run_conversion. Behavior: change. Source scope: paths. Preview: preview_conversion.

Controls: Original files: Keep originals; Archive originals; Replace originals (default keep)

Fixed engine settings: {"preset": "avif_jpeg"}

GIF to MP4

Preview matching inputs, then convert with explicit original-file handling.

Location: Superuser > search "GIF to MP4"

Operation: run_conversion. Behavior: change. Source scope: paths. Preview: preview_conversion.

Controls: Original files: Keep originals; Archive originals; Replace originals (default keep)

Fixed engine settings: {"preset": "gif_mp4"}

WAV to FLAC

Preview matching inputs, then convert with explicit original-file handling.

Location: Superuser > search "WAV to FLAC"

Operation: run_conversion. Behavior: change. Source scope: paths. Preview: preview_conversion.

Controls: Original files: Keep originals; Archive originals; Replace originals (default keep)

Fixed engine settings: {"preset": "wav_flac"}

Catalog: Media transforms

Extract audio

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Extract audio"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Fixed engine settings: {"tool": "extract-audio"}

Mute video

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Mute video"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Fixed engine settings: {"tool": "mute-video"}

Remux video

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Remux video"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Fixed engine settings: {"tool": "remux-video"}

Trim video

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Trim video"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Controls: **Start time** (default 00:00:00) / **Duration** (default 00:00:30)

Fixed engine settings: {"tool": "trim-video"}

Make GIF

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Make GIF"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Fixed engine settings: {"tool": "make-gif"}

Downscale video

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Downscale video"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Controls: **FFmpeg dimensions** (default 1920:-2)

Fixed engine settings: {"tool": "downscale-video"}

Change video speed

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Change video speed"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Controls: **Speed:** 0.5; 1; 1.5; 2; 4 (default 2)

Fixed engine settings: {"tool": "change-speed"}

Deinterlace video

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Deinterlace video"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Fixed engine settings: {"tool": "deinterlace-video"}

Strip media metadata

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Strip media metadata"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Fixed engine settings: {"tool": "strip-metadata"}

Normalize audio

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Normalize audio"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Fixed engine settings: {"tool": "normalize-audio"}

Denoise audio

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Denoise audio"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Fixed engine settings: {"tool": "denoise-audio"}

Reframe vertical video

Preview source files and run the existing transform into separate output files.

Location: Superuser > search "Reframe vertical video"

Operation: run_media_tool. Behavior: change. Source scope: paths. Preview: preview_media_tool.

Fixed engine settings: {"tool": "convert-aspect"}

Catalog: Folder engine

Repair incorrect extensions

Inspect confirmed candidates, then apply the source-checked single-use review through the existing transfer and undo layer.

Location: Superuser > search "Repair incorrect extensions"

Operation: run_file_diagnostics. Behavior: change. Source scope: paths. Preview: scan_file_diagnostics. Requires current previewId.

Fixed engine settings: {"kind": "extensions", "depth": "quick"}

Quarantine broken symbolic links

Inspect confirmed candidates, then apply the source-checked single-use review through the existing transfer and undo layer.

Location: Superuser > search "Quarantine broken symbolic links"

Operation: run_file_diagnostics. Behavior: change. Source scope: paths. Preview: scan_file_diagnostics. Requires current previewId.

Fixed engine settings: {"kind": "symlinks", "depth": "quick"}

Resolve JPEG and RAW companions

Preview paired camera files and choose which format to keep.

Location: Superuser > search "Resolve JPEG and RAW companions"

Operation: resolve_jpeg_raw_pairs. Behavior: change. Source scope: paths. Preview: preview_jpeg_raw_pairs.

Controls: Keep format: raw; jpeg (default raw)

Resolve same-shot container copies

Keep the largest copy and move smaller container siblings to Trash.

Location: Superuser > search "Resolve same-shot container copies"

Operation: resolve_container_pairs. Behavior: change. Source scope: paths. Preview: preview_container_pairs.

Flatten nested folders

Move nested files up while optionally preserving programming projects.

Location: Superuser > search "Flatten nested folders"

Operation: run_flatten_job. Behavior: change. Source scope: paths. Preview: preview_flatten_job.

Controls: Keep programming projects intact (default On)

Catalog: Media analysis

Inspect file health

Report confirmed corruption separately from unsupported, unreadable and inconclusive results.

Location: Superuser > search "Inspect file health"

Operation: scan_file_diagnostics. Behavior: inspect. Source scope: paths. Review evidence is required before resolving candidates.

Controls: **Diagnostic:** corruption; extensions; symlinks (default corruption) / **Inspection depth:** quick; deep (default deep)

Audit audio container inventory

Count eligible audio files using the legacy batch inventory. This does not measure a spectrum.

Location: Superuser > search "Audit audio container inventory"

Operation: run_batch_lossless_audit. Behavior: inspect. Source scope: paths.

Inspect all signals for a file

Photo sharpness and hashes; audio loudness, peaks, tempo and key; video anomalies; document text, language and entities; ZIP safety.

Location: Superuser > search "Inspect all signals for a file"

Operation: content_intelligence_analyze_file. Behavior: inspect. Source scope: file.

Generate a photo preview

Use the shared libvips preview and orientation path.

Location: Superuser > search "Generate a photo preview"

Operation: generate_photo_preview. Behavior: inspect. Source scope: file.

Generate a library thumbnail

Generate a shared document, music or video thumbnail.

Location: Superuser > search "Generate a library thumbnail"

Operation: generate_library_thumbnail. Behavior: inspect. Source scope: file.

Controls: **File type:** document; audio; video (default document)

Read the latest measured audio report

Read the stored report source, creation time and every measured track result.

Location: Superuser > search "Read the latest measured audio report"

Operation: get_latest_audio_results. Behavior: inspect. Source scope: none.

Catalog: Organisation engine

Autosort by type or content

Preview category routing and move matching files through the existing sorter.

Location: Superuser > search "Autosort by type or content"

Operation: run_autosort. Behavior: change. Source scope: paths. Preview: preview_autosort.

Controls: **Classification:** type; content (default type) / **Flatten subfolders** (default Off) / **Destination folder:** path [optional]

Custom folder and filename organisation

Use every supported naming token, date calendar and media type.

Location: Superuser > search "Custom folder and filename organisation"

Operation: run_organise. Behavior: change. Source scope: paths. Preview: preview_organisation.

Controls: **File type:** Photos; Videos; Music; Documents (default photo) / **Folder token pattern** (default {year}/{month}) /

Filename token pattern (optional) / **Calendar:** international; us (default international) / **Destination folder:** path [optional] /

Exact file selection (optional): json

Rename from content and metadata

Preview every same-folder rename, then apply the single-use, source-checked preview.

Location: Superuser > search "Rename from content and metadata"

Operation: run_auto_rename. Behavior: change. Source scope: paths. Preview: preview_auto_rename. Requires current previewId.

Inspect all naming tokens

Read capture dates, camera information, audio tags, document attributes and supported tokens.

Location: Superuser > search "Inspect all naming tokens"

Operation: probe_organisation_tokens. Behavior: inspect. Source scope: file.

Catalog: Text and speech

Extract local text or OCR

Extract PDF, DOCX and plain text; use installed system OCR when available.

Location: Superuser > search "Extract local text or OCR"

Operation: extract_media_text. Behavior: inspect. Source scope: file.

Transcribe a recording

Run the installed local whisper-cli adapter; availability is reported by the engine.

Location: Superuser > search "Transcribe a recording"

Operation: transcribe_media. Behavior: inspect. Source scope: file.

Catalog: Engine status

Inspect bundled analysis assets

Inspect versions, availability and integrity of the bundled local models.

Location: Superuser > search "Inspect bundled analysis assets"

Operation: content_intelligence_status. Behavior: inspect. Source scope: none.

Inspect media backend

Report the active FFmpeg and FFprobe versions and runtime source.

Location: Superuser > search "Inspect media backend"

Operation: check_media_backend. Behavior: inspect. Source scope: none.

Inspect CLIP installation

Check local model availability without downloading anything.

Location: Superuser > search "Inspect CLIP installation"

Operation: get_vision_status. Behavior: inspect. Source scope: none.

Install CLIP visual search

Download the existing ~610 MB visual model when requested.

Location: Superuser > search "Install CLIP visual search"

Operation: ensure_vision_model. Behavior: download. Source scope: none.

Catalog: Inventory and relationships

Index one folder

Build the local SQLite inventory, duplicate relationships, file families and cleanup recommendations.

Location: Superuser > search "Index one folder"

Operation: content_intelligence_scan_folder. Behavior: inspect. Source scope: folder.

Controls: Maximum files (0 for no limit): 0-9007199254740991 (default 0)

Queue background folder indexing

Queue roots in the shared incremental scanner.

Location: Superuser > search "Queue background folder indexing"

Operation: content_intelligence_start_scan. Behavior: inspect. Source scope: paths.

Read background indexing status

Inspect the current queue state and discovered-file counts.

Location: Superuser > search "Read background indexing status"

Operation: content_intelligence_scan_status. Behavior: inspect. Source scope: paths.

Read saved file observations

Read saved measurements and their recorded evidence for an indexed file ID.

Location: Superuser > search "Read saved file observations"

Operation: content_intelligence_get_observations. Behavior: inspect. Source scope: none.

Controls: **Indexed file ID:** 1-9007199254740991 (default 1)

Read every saved file relationship

Inspect exact duplicates, companions and file-family evidence in the shared index.

Location: Superuser > search "Read every saved file relationship"

Operation: content_intelligence_get_relationships. Behavior: inspect. Source scope: none.

Inspect scoped relationships and recommendations

Read indexed file families, duplicates and cleanup evidence for chosen folders.

Location: Superuser > search "Inspect scoped relationships and recommendations"

Operation: content_intelligence_get_folder_insights. Behavior: inspect. Source scope: paths.

Read cleanup recommendations

Inspect pending, accepted or ignored recommendations without applying them.

Location: Superuser > search "Read cleanup recommendations"

Operation: content_intelligence_get_recommendations. Behavior: inspect. Source scope: none.

Controls: **Decision state:** All states; Pending review; Accepted; Ignored

Estimate file compression potential

Read the extension-based heuristic estimate; this does not trial-encode a file.

Location: Superuser > search "Estimate file compression potential"

Operation: content_intelligence_estimate_compression. Behavior: inspect. Source scope: file.

Browse the shared media inventory

Inspect a paginated selection with file-type and text filters.

Location: Superuser > search "Browse the shared media inventory"

Operation: list_imported_media. Behavior: inspect. Source scope: paths.

Controls: **File type:** Photos; Videos; Music; Documents (default photo) / **Page offset:** 0-10000000 (default 0) / **Page size:** 1-1000 (default 100) / **Search filter**

Refresh imported-folder cache

Discard cached import listings for these roots; source files remain untouched.

Location: Superuser > search "Refresh imported-folder cache"

Operation: clear_import_cache. Behavior: inspect. Source scope: paths.

List recent media

Read the supported recent-media query and limit.

Location: Superuser > search "List recent media"

Operation: list_recent_media. Behavior: inspect. Source scope: none.

Controls: **File type:** Photos; Videos; Music; Documents (default photo) / **Maximum results:** 1-1000 (default 30)

List recent imported folders

Read recent folders without starting an import.

Location: Superuser > search "List recent imported folders"

Operation: list_recent_folders. Behavior: inspect. Source scope: none.

Controls: **Maximum results:** 1-1000 (default 30)

Catalog: Storage engine

List mounted storage roots

Inspect available drives and home folders.

Location: Superuser > search "List mounted storage roots"

Operation: list_storage_roots. Behavior: inspect. Source scope: none.

Inspect storage categories

Measure selected roots with coverage information and an optional modification-age filter.

Location: Superuser > search "Inspect storage categories"

Operation: inspect_storage. Behavior: inspect. Source scope: paths.

Controls: **At least this many days old (0 for any):** 0-365000 (default 0) / **At most this many days old (0 for any):** 0-365000 (default 0)

Scan the storage size tree

Measure selected roots with coverage information and an optional modification-age filter.

Location: Superuser > search "Scan the storage size tree"

Operation: scan_storage_tree. Behavior: inspect. Source scope: paths.

Controls: **At least this many days old (0 for any):** 0-365000 (default 0) / **At most this many days old (0 for any):** 0-365000 (default 0)

Scan storage with insights

Measure selected roots with coverage information and an optional modification-age filter.

Location: Superuser > search "Scan storage with insights"

Operation: scan_storage_workspace. Behavior: inspect. Source scope: paths.

Controls: **At least this many days old (0 for any):** 0-365000 (default 0) / **At most this many days old (0 for any):** 0-365000 (default 0)

Compress a storage category

Apply the shared Balanced engine for the chosen category. Smaller verified outputs replace originals, which move to Trash.

Location: Superuser > search "Compress a storage category"

Operation: run_storage_compress. Behavior: destructive. Source scope: paths.

Controls: **File category:** Photos; Videos; Music; Documents (default photos)

Move, copy or trash explicit paths

Use the shared protected-path, collision and undo-aware storage transfer.

Location: Superuser > search "Move, copy or trash explicit paths"

Operation: relocate_storage_entries. Behavior: change. Source scope: paths.

Controls: **Transfer:** copy; move; trash (default copy) / **Destination folder:** path [optional]

Catalog: Camera engine

List camera and removable volumes

Inspect removable sources available for ingest.

Location: Superuser > search "List camera and removable volumes"

Operation: list_ingest_volumes. Behavior: inspect. Source scope: none.

Preview camera bursts and destination paths

Inspect the existing capture grouping, duplicates and ingest destinations.

Location: Superuser > search "Preview camera bursts and destination paths"

Operation: preview_ingest. Behavior: inspect. Source scope: paths.

Controls: **Destination folder:** path [optional]

Match a card against existing libraries

Read the existing library-matching evidence before copying a card.

Location: Superuser > search "Match a card against existing libraries"

Operation: match_ingest_against_library. Behavior: inspect. Source scope: folder.

Controls: **Existing library folders:** paths

Copy or move a reviewed camera import

Preview bursts and paths, then execute with the selected keep list and transfer policy.

Location: Superuser > search "Copy or move a reviewed camera import"

Operation: run_ingest. Behavior: change. Source scope: paths. Preview: preview_ingest.

Controls: **Destination folder:** path [optional] / **Exact files to keep (empty uses all):** json (default []) / **Transfer mode:** copy; move (default copy) / **Keep suggested burst representatives** (default Off)

Catalog: Folder automation

Read saved Live Folder workflows

Inspect complete saved rules, schedules, conditions, actions and pause state.

Location: Superuser > search "Read saved Live Folder workflows"

Operation: get_watch_folders. Behavior: inspect. Source scope: none.

Preview a Live Folder draft

Evaluate the existing workflow planner against a full draft without changing files.

Location: Superuser > search "Preview a Live Folder draft"

Operation: preview_live_folder. Behavior: inspect. Source scope: none.

Controls: **Live Folder draft:** json

Inspect Live Folder processing memory

Read per-item processing state, signatures and retry diagnostics.

Location: Superuser > search "Inspect Live Folder processing memory"

Operation: live_folder_rule_status. Behavior: inspect. Source scope: none.

Controls: Live Folder draft: json

Test one Live Folder rule

Inspect nested condition diagnostics for one file without executing actions.

Location: Superuser > search "Test one Live Folder rule"

Operation: test_live_folder_rule. Behavior: inspect. Source scope: none.

Controls: Live Folder draft: json / **Rule index (starts at 0):** 0-10000 (default 0) / **File or folder to test:** path

Run a saved Live Folder now

Execute the saved rule order with existing collision protection and processing memory.

Location: Superuser > search "Run a saved Live Folder now"

Operation: run_live_folder_now. Behavior: change. Source scope: folder.

Pause or resume a Live Folder

Change the saved pause state without replacing its draft rules.

Location: Superuser > search "Pause or resume a Live Folder"

Operation: set_live_folder_paused. Behavior: change. Source scope: folder.

Controls: Pause workflow (default On)

Read a Live Folder rule file

Validate and import a rule file into the result for inspection. Imported rules start disabled.

Location: Superuser > search "Read a Live Folder rule file"

Operation: import_live_folder_rules. Behavior: inspect. Source scope: file.

Export Live Folder rules

Write a versioned rule file without overwriting existing exports.

Location: Superuser > search "Export Live Folder rules"

Operation: export_live_folder_rules. Behavior: change. Source scope: folder.

Controls: Rules to export: json (default [])

Catalog: Operation journal

Read undoable transactions

Inspect durable undo records, including operations from previous app sessions.

Location: Superuser > search "Read undoable transactions"

Operation: list_undoable_transactions. Behavior: inspect. Source scope: none.

Undo a specific transaction

Reverse a recorded transaction using its journal ID.

Location: Superuser > search "Undo a specific transaction"

Operation: undo_operation. Behavior: change. Source scope: none.

Controls: Undo transaction ID

Check for active operations

Inspect whether any operation leases are still active.

Location: Superuser > search "Check for active operations"

Operation: has_active_operations. Behavior: inspect. Source scope: none.

Catalog: Deep Cleanup engine

Inspect every available cleanup rule

Read engine capabilities, unsupported providers and recovery notices.

Location: Superuser > search "Inspect every available cleanup rule"

Operation: system_cleaner_capabilities. Behavior: inspect. Source scope: none.

Read Deep Cleanup history

Read the most recent stored outcome summaries.

Location: Superuser > search "Read Deep Cleanup history"

Operation: system_cleaner_history. Behavior: inspect. Source scope: none.

Scan every Deep Cleanup provider

Use standard, selected-folder or custom-rule scope, including exclusions and custom rule conditions.

Location: Superuser > search "Scan every Deep Cleanup provider"

Operation: scan_system_cleaner. Behavior: inspect. Source scope: none.

Controls: Cleanup scan request: json (default {"scope": "standard", "roots": [], "excludedPaths": [], "excludedNames": [], "customRules": []})

Plan and execute reviewed Deep Cleanup

Prepare a single-use plan from scan/source IDs. The existing engine enforces plan expiry and removal mode.

Location: Superuser > search "Plan and execute reviewed Deep Cleanup"

Operation: run_system_cleaner. Behavior: destructive. Source scope: none. Preview: preview_system_cleaner. Requires current planId.

Controls: Reviewed scan selection: json (default {"scanId": "", "sourceIds": [], "removalMode": "trash"}) / Confirm permanent removal when the reviewed plan requires it (default Off)

Catalog: Algorithm lab

Image Laplacian sharpness

Laplacian edge variance on exact grayscale pixels.

Location: Superuser > search "Image Laplacian sharpness"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Sample width:** 1-65535 (default 9) / **Sample height:** 1-65535 (default 8) / **Grayscale pixels:** json (default [])

Fixed engine settings: {"algorithm": "image_sharpness"}

Image luminance and clipping

Percentile range and dark/bright clipping fractions.

Location: Superuser > search "Image luminance and clipping"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Grayscale pixels:** json (default [])

Fixed engine settings: {"algorithm": "image_luminance"}

Image difference hash

Compute a 64-bit dHash from exactly 9 × 8 grayscale pixels.

Location: Superuser > search "Image difference hash"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **72 grayscale pixels:** json (default [])

Fixed engine settings: {"algorithm": "image_dhash"}

Image perceptual DCT hash

Compute the shared 63-bit pHash with RustDCT from a 32 × 32 grayscale sample.

Location: Superuser > search "Image perceptual DCT hash"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **1,024 grayscale pixels:** json (default [])

Fixed engine settings: {"algorithm": "image_phash"}

Hash Hamming distance

Count different bits between two hexadecimal image hashes.

Location: Superuser > search "Hash Hamming distance"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **First 16-digit hash** / **Second 16-digit hash**

Fixed engine settings: {"algorithm": "hash_distance"}

Quantized dominant color palette

Inspect the existing 32-step RGB color clusters and fractions.

Location: Superuser > search "Quantized dominant color palette"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **RGB pixel triplets:** json (default []) / **Colors to return:** 1-64 (default 5)

Fixed engine settings: {"algorithm": "image_palette"}

Image kind heuristic

Classify photo, screenshot, scan or meme from supplied measurements.

Location: Superuser > search "Image kind heuristic"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Sample width:** 1-65535 (default 9) / **Sample height:** 1-65535 (default 8) / **Camera EXIF present** (default Off) / **Transparency present** (default Off) / **Laplacian variance:** 0-1000000 (default 0) / **Unique-color fraction:** 0-1 (default 0.5)

Fixed engine settings: {"algorithm": "image_classification"}

Complete image signal analysis

Run image classification, sharpness, range, dHash and palette together.

Location: Superuser > search "Complete image signal analysis"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Sample width:** 1-65535 (default 9) / **Sample height:** 1-65535 (default 8) / **RGB pixel triplets:** json (default []) / **Camera EXIF present** (default Off) / **Transparency present** (default Off)

Fixed engine settings: {"algorithm": "image_signals"}

Text normalization

Run the shared whitespace and case normalization used in matching.

Location: Superuser > search "Text normalization"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Text

Fixed engine settings: {"algorithm": "text_normalization"}

Text SimHash

Compute the existing 64-bit token similarity hash.

Location: Superuser > search "Text SimHash"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Text

Fixed engine settings: {"algorithm": "text_simhash"}

Offline text language estimate

Inspect the local language code and confidence.

Location: Superuser > search "Offline text language estimate"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Text

Fixed engine settings: {"algorithm": "text_language"}

Document type heuristic

Classify invoice, receipt, contract, paper, spreadsheet or presentation.

Location: Superuser > search "Document type heuristic"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Text / **File extension** (default txt)

Fixed engine settings: {"algorithm": "document_type"}

Document dates and amounts

Extract bounded date, monetary amount and currency candidates.

Location: Superuser > search "Document dates and amounts"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Text

Fixed engine settings: {"algorithm": "document_entities"}

Approximate audio loudness

Run the RMS-based LUFS approximation; not a calibrated R128 meter.

Location: Superuser > search "Approximate audio loudness"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Signed 16-bit mono PCM samples: json (default []) / PCM sample rate (Hz): 8000-192000 (default 11025)

Fixed engine settings: {"algorithm": "audio_loudness"}

Audio peak and clipping

Measure peak dBFS and the number of clipped samples.

Location: Superuser > search "Audio peak and clipping"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Signed 16-bit mono PCM samples: json (default []) / PCM sample rate (Hz): 8000-192000 (default 11025)

Fixed engine settings: {"algorithm": "audio_peak"}

Audio silent spans

Inspect the existing silence-window heuristic.

Location: Superuser > search "Audio silent spans"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Signed 16-bit mono PCM samples: json (default []) / PCM sample rate (Hz): 8000-192000 (default 11025)

Fixed engine settings: {"algorithm": "audio_silence"}

Audio tempo estimate

Run the existing onset-envelope BPM estimate.

Location: Superuser > search "Audio tempo estimate"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Signed 16-bit mono PCM samples: json (default []) / PCM sample rate (Hz): 8000-192000 (default 11025)

Fixed engine settings: {"algorithm": "audio_tempo"}

Audio musical-key estimate

Run the existing single-octave pitch-class estimate.

Location: Superuser > search "Audio musical-key estimate"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Signed 16-bit mono PCM samples: json (default []) / PCM sample rate (Hz): 8000-192000 (default 11025)

Fixed engine settings: {"algorithm": "audio_key"}

Speech-versus-music heuristic

Inspect the zero-crossing speech-likeness flag.

Location: Superuser > search "Speech-versus-music heuristic"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Signed 16-bit mono PCM samples:** json (default []) / **PCM sample rate (Hz):** 8000-192000 (default 11025)

Fixed engine settings: {"algorithm": "audio_speech"}

Chromaprint display fingerprint

Fingerprint sufficient varied audio with shared preset test2; silent/short data returns no evidence.

Location: Superuser > search "Chromaprint display fingerprint"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Signed 16-bit mono PCM samples:** json (default []) / **PCM sample rate (Hz):** 8000-192000 (default 11025)

Fixed engine settings: {"algorithm": "audio_fingerprint"}

Chromaprint recording sequence match

Compare two PCM samples using offset-aware matching, strong-segment score and 85% coverage.

Location: Superuser > search "Chromaprint recording sequence match"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Signed 16-bit mono PCM samples:** json (default []) / **Second signed 16-bit PCM sample:** json (default []) / **PCM sample rate (Hz):** 8000-192000 (default 11025)

Fixed engine settings: {"algorithm": "audio_recording_match"}

Video sample timestamp planner

Generate the bounded shot/keyframe sample points used by analysis.

Location: Superuser > search "Video sample timestamp planner"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Duration (seconds):** 0-100000000 (default 180) / **Maximum sample shots:** 1-128 (default 8)

Fixed engine settings: {"algorithm": "video_sampling"}

Temporal video hash

Hash an ordered sequence of frame hashes.

Location: Superuser > search "Temporal video hash"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Ordered frame-hash strings:** json (default [])

Fixed engine settings: {"algorithm": "video_temporal_hash"}

Video footage heuristic

Classify screen recording, gameplay or camera footage from supplied measurements.

Location: Superuser > search "Video footage heuristic"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Sample width:** 1-65535 (default 9) / **Sample height:** 1-65535 (default 8) / **Frames per second:** 0-1000 (default 30) / **Codec** (default h264) / **Has audio** (default On) / **Shakiness score:** 0-1 (default 0)

Fixed engine settings: {"algorithm": "video_classification"}

Video bits per pixel per frame

Calculate encoding density from bitrate, dimensions and frame rate.

Location: Superuser > search "Video bits per pixel per frame"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Sample width:** 1-65535 (default 9) / **Sample height:** 1-65535 (default 8) / **Bitrate (bits per second):** 0-100000000000 (default 8000000) / **Frames per second:** 0-1000 (default 30)

Fixed engine settings: {"algorithm": "video_density"}

Parse video anomaly intervals

Parse blackdetect, freezedetect or silencedetect log evidence.

Location: Superuser > search "Parse video anomaly intervals"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Text / FFmpeg filter:** blackdetect; freezedetect; silencedetect (default blackdetect)

Fixed engine settings: {"algorithm": "video_anomalies"}

L2 vector normalization

Run the same normalization used by local visual embeddings.

Location: Superuser > search "L2 vector normalization"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Vector:** json (default [])

Fixed engine settings: {"algorithm": "vector_normalization"}

Vector cosine comparison

Normalize equal-dimension vectors and compute their cosine similarity.

Location: Superuser > search "Vector cosine comparison"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Vector:** json (default []) / **Second vector:** json (default [])

Fixed engine settings: {"algorithm": "vector_cosine"}

CLIP query expansion

Inspect the exact visual prompt generated from a search phrase.

Location: Superuser > search "CLIP query expansion"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Text**

Fixed engine settings: {"algorithm": "visual_query"}

CLIP RGB preprocessing

Convert a 224 × 224 RGB frame to the existing normalized NCHW tensor.

Location: Superuser > search "CLIP RGB preprocessing"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **224 × 224 RGB pixel triplets:** json (default [])

Fixed engine settings: {"algorithm": "clip_preprocessing"}

Compute a full file SHA-256

Stream every byte through the shared cancellable SHA-256 reader.

Location: Superuser > search "Compute a full file SHA-256"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Source file:** path

Fixed engine settings: {"algorithm": "file_sha256"}

Compute a sampled file signature

Read the shared segmented signature; this is not a full-file digest.

Location: Superuser > search "Compute a sampled file signature"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Source file:** path

Fixed engine settings: {"algorithm": "file_quick_signature"}

Inspect physical file identity

Read the OS identity used to distinguish hard links from separate copies.

Location: Superuser > search "Inspect physical file identity"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Source file:** path

Fixed engine settings: {"algorithm": "file_identity"}

Verify a file header

Check known file-opening signatures against the file extension.

Location: Superuser > search "Verify a file header"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Source file:** path

Fixed engine settings: {"algorithm": "file_header"}

Inspect ZIP archive safety

Read entry names, sizes, path-traversal and expansion-ratio evidence without extracting.

Location: Superuser > search "Inspect ZIP archive safety"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Source file:** path

Fixed engine settings: {"algorithm": "archive_manifest"}

Inspect PDF text coverage

Read page count, scanned-document evidence and a bounded text sample.

Location: Superuser > search "Inspect PDF text coverage"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: **Source file:** path

Fixed engine settings: {"algorithm": "document_structure"}

Extract OOXML XML text

Use the bounded shared Office ZIP/XML extraction path.

Location: Superuser > search "Extract OOXML XML text"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Source file: path

Fixed engine settings: {"algorithm": "document_ooxml"}

Inspect document signals

Read type, language, text coverage, SimHash, dates and monetary candidates.

Location: Superuser > search "Inspect document signals"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Source file: path

Fixed engine settings: {"algorithm": "document_signals"}

Inspect complete document matching evidence

Read exact normalized-text and SimHash evidence only when extraction is complete.

Location: Superuser > search "Inspect complete document matching evidence"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Source file: path

Fixed engine settings: {"algorithm": "document_matching_signals"}

Inspect stacked file classification

Run filename, location, header and text classification with confidence and rationale.

Location: Superuser > search "Inspect stacked file classification"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Source file: path

Fixed engine settings: {"algorithm": "file_classification"}

Inspect CLIP token IDs and masks

Use the exact installed tokenizer, including normalization, BPE and its 77-position attention mask.

Location: Superuser > search "Inspect CLIP token IDs and masks"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Text

Fixed engine settings: {"algorithm": "clip_tokenization"}

Compute a local CLIP text embedding

Run the installed text encoder with no automatic model download.

Location: Superuser > search "Compute a local CLIP text embedding"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Text

Fixed engine settings: {"algorithm": "clip_text_embedding"}

Compute a local CLIP image embedding

Run the installed image encoder on exactly 224 × 224 RGB pixels.

Location: Superuser > search "Compute a local CLIP image embedding"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: 224 × 224 RGB pixel triplets: json (default [])

Fixed engine settings: {"algorithm": "clip_image_embedding"}

Filename query fallback

Inspect the filename-only fallback used by visual search.

Location: Superuser > search "Filename query fallback"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Filename or path / Text

Fixed engine settings: {"algorithm": "filename_query"}

Visual folder index key

Inspect the stable local key used for a visual-search root.

Location: Superuser > search "Visual folder index key"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Folder path

Fixed engine settings: {"algorithm": "folder_index_key"}

Parse content label aliases

Inspect supported aliases and the resulting academic, work, personal or clutter labels.

Location: Superuser > search "Parse content label aliases"

Operation: run_superuser_algorithm. Behavior: inspect. Source scope: none.

Controls: Text

Fixed engine settings: {"algorithm": "content_label_parsing"}